

Submit 3 Copies To Appropriate District
Office:
District I
1625 N. French Dr., Hobbs, NM 88240
District II
811 South First, Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM
87505

State of New Mexico
Energy, Minerals and Natural Resources

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

Form C-103

Revised March 25, 1999

WELL API NO.

30-015-32362

5. Indicate Type of Lease

STATE ☒ FEE ☐

6. State Oil & Gas Lease No.

E-10165

7. Lease Name or Unit Agreement Name:

State AU State Com

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

Oil Well ☐ Gas Well ☒ Other ☐

2. Name of Operator

Yates Petroleum Corporation

3. Address of Operator

105 S. 4th Street Artesia, NM 88210

4. Well Location

Unit Letter A : 660 feet from the North line and 660 feet from the East line

Section 33 Township 18S Range 25E NMPM Eddy County

10. Elevation (Show whether DR, RKB, RT, GR, etc.)

3539' GR

11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	MULTIPLE COMPLETION <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>	
OTHER: <input type="checkbox"/>		OTHER: Set surface and Intermediate casing <input checked="" type="checkbox"/>	

Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompilation.

8/9/02 - TD 17-1/2" hole at 12:15 AM. Ran 9 joints 13-3/8" 48# H-40 casing set at 385'. Texas Pattern Guide shoe set at 385'. Insert float set at 340'. Cemented with 450 sx Class "C" with additives. PD at 4:45 AM. Circulated 33 sx. WOC 18 hours. Reduced hole to 12-1/4" and resumed drilling.

8/11/02 - TD 12-1/4" hole at 12:15 PM. Ran 29 joints 8-5/8" 24# J-55 casing set at 1210'. Texas Pattern Guide shoe set at 1198'. Insert float set at 1156'. Rigged up BJ and circulated. Hole bridged off while pumping - work tight hole. 1" cement. Work stuck casing. Rigged up rotary wireline. Run free point (casing stuck at shoe joint, pipe free down to insert float). Work stuck casing. Received verbal permission from Van Barton with OCD in Artesia to perforate casing and cement. Rigged up rotary wireline and perforate casing. Shot 4-1/2" holes at 1145'. Rigged up BJ and circulate. Cemented with 200 sx "H" with additives and 700 sx Class "C" Lite Poz with additives. Tailed in with 200 sx Class "C" with additives. PD at 5:45 PM. Did not circulate cement. Rig up and run temperature survey (top of cement 450'). Cement with 1" pipe. Tagged cement at 450'.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Tina Huerta TITLE Regulatory Compliance Supervisor DATE August 14, 2002

Type or print name Tina Huerta

Telephone No. 505-748-1471

(This space for State use)

ORIGINAL SIGNED BY TIM W. GUM
DISTRICT II SUPERVISOR

APPROVED BY BA

TITLE

DATE

Conditions of approval, if any:

AUG 26 2002

YATES PETROLEUM CORPORATION
State AU State Com #2
33-T18S-R25E
Eddy County, New Mexico

SUNDRY NOTICE CONTINUED:

8/12/02 – Ran 1". Tagged cement at 450'. Spotted 50 sx of Class "C" with additives. Stopped pumping at 2:15 AM. WOC 1-3/4 hours. Ran 1". Tagged cement at 435'. Spotted 25 sx Class "C" with additives. Stopped pumping at 4:15 AM. WOC 2-1/2 hours. Ran 1". Tagged cement at 410'. Spotted 50 sx Class "C" with additives. Stopped pumping at 7:10 AM. WOC 1 hour. Ran 1". Tagged cement at 290'. Spotted 75 sx Class "C" Neat cement. Stopped pumping at 8:20 AM. Circulated 10 sx to pit on 4th stage. Tagged cement at 1009'. Drilled out at 1:00 AM 8/13/02. WOC 43 hours and 15 mins. Reduced hole to 7-7/8" and resumed drilling.


Tina Huerta
Regulatory Compliance Supervisor
August 14, 2002