

Submit 3 Copies To Appropriate District
Off. :
District I
1625 N. French Dr., Hobbs, NM 88240
District II
811 South First, Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM
87505

State of New Mexico
Energy, Minerals and Natural Resources

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

Form C-103

Revised March 25, 1999

WELL API NO.

30-015-32362

5. Indicate Type of Lease

STATE ☒

FEE ☐

6. State Oil & Gas Lease No.

E-10165

7. Lease Name or Unit Agreement Name:

State AU State Com

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH
PROPOSALS.)

1. Type of Well:

Oil Well ☐

Gas Well ☒

Other ☐

2. Name of Operator

Yates Petroleum Corporation

3. Address of Operator

105 S. 4th Street Artesia, NM 88210

8. Well No.

2

9. Pool name or Wildcat

Undesignated Boyd Morrow

4. Well Location

Unit Letter A : 660 feet from the North line and 660 feet from the East line

Section

33

Township

18S

Range

25E

NMPM

Eddy

County

10. Elevation (Show whether DR, RKB, RT, GR, etc.)

3539' GR

11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☐

REMEDIAL WORK ☐

ALTERING CASING ☐

TEMPORARILY ABANDON ☐

CHANGE PLANS ☐

COMMENCE DRILLING OPNS. ☐

PLUG AND ABANDONMENT ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETION ☐

CASING TEST AND CEMENT JCB ☐

OTHER: ☐

OTHER: Set production casing ☒

Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

8/28/02 - TD 7-7/8" hole at 2:15 PM. Ran 2 1/2 joints 5-1/2" 15.5# and 17# P110 and J-55 casing set at 9150' as follows: 21 joints SB (898.53'), 37 joints varn (1582.69'), 146 joints varn (6288.42'), 9 joints varn (392.42'). Float shoe set at 9350'. Float collar set at 9105.82'. Bottom marker set at 8533.83'. Cemented with 150 SCF nitrogen and 150 bbls mud ahead of 650 sx BJ Lite "C" (35:65:6) with additives. Tailed in with 650 sx Super "C" Modified (15:61:11) with additives. PD at 7:15 AM 8/29/02. Did not circulate cement. Cement top approximately 1200' according to differential pressure. Rig released at 1:15 PM 8/29/02.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Tina Huerta TITLE Regulatory Compliance Supervisor DATE September 5, 2002

Type or print name Tina Huerta

Telephone No. 505-748-1471

(This space for State use)

ORIGINAL SIGNED BY TIM W. GUM
DISTRICT II SUPERVISOR

APPROVED BY Tina Huerta

TITLE

DATE

SEP 13 2002

Conditions of approval, if any: