

Submit 3 Copies To Appropriate District Office

District I

1625 N. French Dr., Hobbs, NM 88240

District II

1301 W. Grand Ave., Artesia, NM 88210

District III

1000 Rio Brazos Rd., Aztec, NM 87410

District IV

1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

Form C-103

Revised March 25, 1999

WELL API NO.

30-015-32391

5. Indicate Type of Lease

STATE ☒ FEE ☐

6. State Oil & Gas Lease No.

7. Lease Name or Unit Agreement

Name:
Garvin "22" State Com

8. Well No.

2

9. Pool name or Wildcat

Turkey Track; (Morrow) North Gas

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

Oil Well ☐ Gas Well ☒ Other

2. Name of Operator

V-F Petroleum Inc.

3. Address of Operator

P.O. Box 1889 Midland, Texas 79702

4. Well Location

Unit Letter L : 660 feet from the West line and 1,980 feet from the South line

Section 22 Township 18S Range 28E NMPM Eddy County

10. Elevation (Show whether DR, RKB, RT, GR, etc.)
3,614' GL

11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐ CHANGE PLANS ☐

PULL OR ALTER CASING ☐ MULTIPLE COMPLETION ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☒ PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☒

OTHER: ☐

12. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

7/31/02 Build Location

8/04/02 Spud Key Rig # 37 17 1/2" hole.

8/07/02 Ran 11 jts 13 3/8" 48# ST&C @ 450'. Cement w/200 sxs 35/65 poz-C + 2% CaCl2 + 1/4 Cello + 6% gel + 200 sxs Class C + 2% CaCl2. Circ 100 sxs to pit. Disp plug with FW. PD @ 3:45 am floats held. Drill out w/ 11" hole after WOC.

8/13/02 Ran 80 jts 8 5/8" 32# J-55 ST&C @ 3,154'. Cement w/1,100 sxs 35/65-C + 2% CaCl2 + 1/4 Cello + 6% gel + 200 sxs Class G + 2% CaCl2 + .005 FP-6L. Circ 400 sxs to pit. Disp plug with FW. PD @ 1:45 pm, floats held. Drill out w/ 7-7/8" hole after WOC.

9/09/02 Ran 215 jts 7" 26# L-80 @ 9,067'. Cement w/ 200 sxs Class H + 1% BA10 + 0.6% CD32 with partial returns. Disp plug with FW. PD @ 5:45 am, floats held. Drill out w/ 6-1/8" hole.

9/21/02 Ran open hole logs @ TD 11,100'.

9/22/02 Ran 261 jts 4 1/2" 11.6# P-110 & L-80 @ 11,100'. Cement w/350 sxs Class H + 1% BA58 + 3% CD-32 + 1% EC-1 + 1% salt with full returns. Disp plug with FW. PD @ 8:22 am, floats held.

9/23/02 Rig released.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Larry Brazile TITLE Petroleum Engineer DATE 10/02/02

Type or print name Larry Brazile Telephone No. (915)-683-3344

(This space for State use)

APPROVED BY APR TITLE DATE

Conditions of approval, if any: