

Form 9-381a  
(Feb. 1961)COPY TO:  
(SUBMIT IN TRIPPLICATE)  
STATE WATER ENGLand Office New MexicoLease No. 72-964142U.S. 7UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEYAPPROVED  
MAR 22 1963  
A. R. BRUNN  
DISTRICT ENGINEER

## SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL.....	SUBSEQUENT REPORT OF WATER SHUT-OFF.....
NOTICE OF INTENTION TO CHANGE PLANS.....	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.....
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....	SUBSEQUENT REPORT OF ALTERING CASING.....
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.....	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR.....
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....	SUBSEQUENT REPORT OF ABANDONMENT.....
NOTICE OF INTENTION TO PULL OR ALTER CASING.....	SUPPLEMENTARY WELL HISTORY.....
NOTICE OF INTENTION TO ABANDON WELL.....	
<u>Notice of Intention to Re-Enter</u> .....	<u>X</u>

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

Well No. 1 is located 1900 ft. from N line and 1900 ft. from W line of sec. 3  
34 of N. 4, Sec. 3  
 (1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)

Un designated (Field) 34 (County or Subdivision) New Mexico (State or Territory)

The elevation of the derrick floor above sea level is 3760 ft.

## DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Notice is hereby given of intention to re-enter the subject well, procedure as follows:

1. Move in and rig up rotary rig.
2. Repair 13-3/8" casing at surface, install casinghead and blowout preventer equipment.
3. Drill out cement plugs to 1500'. Run 8-3/4" bit and attempt to enter 9-5/8" casing at 1500 feet. If successful, drill out cement plugs and clean out to 9100'.
4. Spot 30 ac cement plug 9100-9300 ft. WOC 4 hours and check plug. Drill out to approximately 9000 ft.
5. Run and cement 13" casing at PWD using stage collar at 1500 ft.
6. WOC 16 hours and drill out cement to new PWD. Rig down and move out rotary rig.
7. Proceed to perforate and test Atocha & Guadalupe zones.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Standard Oil Company of Texas, A Division of California Oil CompanyAddress Dresser "B"Mechanics, TexasBy J. L. RowlandTitle District Engineer

1. 10. 1950

2. 11. 1950  
3. 12. 1950  
4. 1. 1951  
5. 2. 1951  
6. 3. 1951  
7. 4. 1951  
8. 5. 1951  
9. 6. 1951  
10. 7. 1951  
11. 8. 1951  
12. 9. 1951  
13. 10. 1951  
14. 11. 1951  
15. 12. 1951  
16. 1. 1952  
17. 2. 1952  
18. 3. 1952  
19. 4. 1952  
20. 5. 1952  
21. 6. 1952  
22. 7. 1952  
23. 8. 1952  
24. 9. 1952  
25. 10. 1952  
26. 11. 1952  
27. 12. 1952  
28. 1. 1953  
29. 2. 1953  
30. 3. 1953  
31. 4. 1953  
32. 5. 1953  
33. 6. 1953  
34. 7. 1953  
35. 8. 1953  
36. 9. 1953  
37. 10. 1953  
38. 11. 1953  
39. 12. 1953  
40. 1. 1954  
41. 2. 1954  
42. 3. 1954  
43. 4. 1954  
44. 5. 1954  
45. 6. 1954  
46. 7. 1954  
47. 8. 1954  
48. 9. 1954  
49. 10. 1954  
50. 11. 1954  
51. 12. 1954  
52. 1. 1955  
53. 2. 1955  
54. 3. 1955  
55. 4. 1955  
56. 5. 1955  
57. 6. 1955  
58. 7. 1955  
59. 8. 1955  
60. 9. 1955  
61. 10. 1955  
62. 11. 1955  
63. 12. 1955  
64. 1. 1956  
65. 2. 1956  
66. 3. 1956  
67. 4. 1956  
68. 5. 1956  
69. 6. 1956  
70. 7. 1956  
71. 8. 1956  
72. 9. 1956  
73. 10. 1956  
74. 11. 1956  
75. 12. 1956  
76. 1. 1957  
77. 2. 1957  
78. 3. 1957  
79. 4. 1957  
80. 5. 1957  
81. 6. 1957  
82. 7. 1957  
83. 8. 1957  
84. 9. 1957  
85. 10. 1957  
86. 11. 1957  
87. 12. 1957  
88. 1. 1958  
89. 2. 1958  
90. 3. 1958  
91. 4. 1958  
92. 5. 1958  
93. 6. 1958  
94. 7. 1958  
95. 8. 1958  
96. 9. 1958  
97. 10. 1958  
98. 11. 1958  
99. 12. 1958  
100. 1. 1959