NEW MEXICO OIL CONSERVATION COMMISSION BOX 2018 207 CARPER BUILDING HOBES, NEW MEXICO ARTES IA, NEW MEXICO

May, 1960 No. A 88

SUPPLEMENT TO THE OIL PRORATION SCHEDULE

DATE May 27, 1960

PURPOSE: ALLOWABLE ASS IGHNERT FOR A NEW WELL

Effective May 18, 1960, an allowable of 44 berrels of oil per day or a total of 616 barrels for the month is hereby assigned to the Pan American Pete Torpe, UEA Yates Pede, 1-1, 3-19-25, #ildcat-Holfcamp Peole

KLA/bh

Pan Amer.

Indiana

OIL CONSERVATION COMMISSION

Supervisor, District No. 2

EXTRA COPY

JOHN W. WEST ENGINEERING COMPANY

412 HORTH DAL PASO HOBBS, NEW MEXICO

April 11, 1960

Pan American Petroleum Gorp. P.O. Bex 68 Hobbs, New Mexico.

Gentlemen:

On April 8, 1960, a survey was made to stake the location for your U.S.A. Yates No. 1 well, at a point 660 feet from the East line and 1980 feet from the South line of Section 3, Twp. 19 South, Rng. 25 East, N.M.P.M., Eddy County, New Mexico.

The transit was "wiggled in" on the half section line between the marked stones set for the East Quarter Section corner and the West Quarter Section corner. Thence chaining West from the East Quarter Section corner a distance of 660 feet and setting a hub with tack at this point. Then we set the transit over said hub and taking a foresight on the East Quarter Section corner. Thence chaining South a distance of 660 feet to the location. As a check on our survey we chained East from the location a distance of 660 feet and North a distance of 659.9 feet to the East Quarter Section corner. This leaves an error of 0.1 feet which is well within the limits of this survey.

The procedure of this survey was determined by the fact that the Southeast corner of said Section 3 could not be found and the Southwest corner was loose and in a doubtful position.

I hereby certify that the foregoing survey was made in the field by me and that the same is true and correct to best of my knowledge and belief.

Respectfully submitted,

John I