

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

NOTICE OF INTENTION TO DRILL

Notice must be given to the Oil Conservation Commission or its proper agent and approval obtained before drilling begins. If changes in the proposed plan are considered advisable, a copy of this notice showing such changes will be returned to the sender. Submit this notice in triplicate. One copy will be returned following approval. See additional instructions in Rules and Regulations of the Commission.

Artesia, New Mexico,

August 19, 1940

Place

Date

OIL CONSERVATION COMMISSION,
Santa Fe, New Mexico.

Gentlemen:

You are hereby notified that it is our intention to commence the drilling of a well to be known as

Dooley & Haynes

Martin

Well No. 1

in SE 1/4 NW 1/4

Company or Operator

Lease

of Sec. 9, T. 19S., R. 25E., N. M. P. M., Wildcat Field, Eddy County

N.

The well is 330 feet (N.) (S.) of the 8 line and 330 feet

(E) (W.) of the E line of NW 1/4 of Section 9

(Give location from section or other legal subdivision lines. Cross out wrong directions)

If state land the oil and gas lease is No. ----- Assignment No. -----

If patented land the owner is William A. Martin et al.

Address Artesia, New Mexico

If government land the permittee is -----

Address -----

The lessee is William Dooley

Address Box 428, Artesia, New Mexico

We propose to drill well with drilling equipment as follows: -----

Cable Tools

The status of a bond for this well in conformance with Rule 39 of the General Rules and Regulations of the Commission is as follows: ~~\$2,500.00~~ **\$2,500.00 Surety Bond**

We propose to use the following strings of casing and to land or cement them as indicated:

Size of Hole	Size of Casing	Weight Per Foot	New or Second Hand	Depth	Landed or Cemented	Sacks Cement
12 in.	10 in.	40 lb.	second hand	50 ft.	Landed	none
	8 1/2"	26 lb.	second hand	300 to 400'	Landed	
	7" O.D.	20 lb.	second hand	Estimated 500 to 600'	Cemented	25 sacks

If changes in the above plan become advisable we will notify you before cementing or landing casing. We estimate that the first productive oil and gas sand should occur at a depth of about 550-650 feet.

Additional information: 10" casing is intended to hold back surface boulders, if necessary. Contract depth of well is 1,000 feet. Will cement production string with 25 sacks of cement and 5 tons oil well mud (Will cement pipe through all surface waters.)

SEP 11 1940

Approved _____, 19_____
except as follows:

Sincerely yours,

Dooley & Haynes

Company or Operator

By

William P. Dooley

Position Partner

Send communications regarding well to

Name William P. Dooley

Address Box 428, Artesia, New Mex.

OIL CONSERVATION COMMISSION

By

Roy Yarbrough
OIL & GAS INSPECTOR

Title

