

NEW MEXICO OIL CONSERVATION COMMISSION  
DRAWER DD  
ARTESIA, NEW MEXICO

PLOGGING  
FIELD REPORT FOR CEMENTING OF WELLS

Operator <u>E.P. CAMPBELL</u>		Lease <u>WILLIS M. BOYD</u>		Well # <u>I</u>	
Location of Well	Unit <u>SESW</u>	Section <u>14</u>	Township <u>19S</u>	Range <u>25E.</u>	County <u>EDDY</u>
<del>Drilling</del> Plugging Contractor <u>SWARTZ</u>		Type of Equipment <u>PLUGGING</u>			

APPROVED CASING PROGRAM

Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
<u>1 3/8</u>	<u>10 3/4"</u>	<u>32.75#</u>	<u>USED</u>	<u>697</u>	<u>TOP Cement 170</u> <u>TEMP. SURVEY</u>
<u>old 10 3/4" casing shot at 810' pumped out &amp; collapsed at 693' therefore there is still 10 3/4"</u>					
<u>Casing from 693' to 1019'. 7 7/8" Hole from 1019' to 6570'</u>					

Casing Data:

Surface \_\_\_\_\_ joints of \_\_\_\_\_ inch \_\_\_\_\_ # Grade \_\_\_\_\_

(Approved) (Rejected) \_\_\_\_\_

Inspected by \_\_\_\_\_ date \_\_\_\_\_

Cementing Program

Size of hole \_\_\_\_\_ Size of Casing \_\_\_\_\_ Sacks cement required \_\_\_\_\_

Type of Shoe used \_\_\_\_\_ Float collar used \_\_\_\_\_ Btm 3 jts welded \_\_\_\_\_

TD of hole 6570 Set \_\_\_\_\_ Feet of \_\_\_\_\_ Inch \_\_\_\_\_ # Grade \_\_\_\_\_

New-used csg. @ \_\_\_\_\_ with \_\_\_\_\_ sacks neat cement around shoe

+ \_\_\_\_\_ sax \_\_\_\_\_ additives \_\_\_\_\_

Plug down @ \_\_\_\_\_ (AM) (PM) Date \_\_\_\_\_

Cement circulated \_\_\_\_\_ No. of Sacks \_\_\_\_\_

Cemented by \_\_\_\_\_ Witnessed by \_\_\_\_\_

Temp. Survey ran @ \_\_\_\_\_ (AM) (PM) Date \_\_\_\_\_ top cement @ \_\_\_\_\_

Casing test @ \_\_\_\_\_ (AM) (PM) Date \_\_\_\_\_

Method Used \_\_\_\_\_ Witnessed by \_\_\_\_\_

Checked for shut off @ \_\_\_\_\_ (AM) (PM) Date \_\_\_\_\_

Method used CEMENT PLOGS VIA TUBING Witnessed by LEBLEY

Remarks:

Hole is to be loaded with mud  
and plugged as follows:

1. 6570' = 25 sks.

2. 3930' = 15 sks.

3. 711' to 677' = 20 sks.