RONNIE E SHOOK BONNIE ENGINEER	(SUBMIT IN TRIPLIC UNITED STAT RTMENT OF THE GEOLOGICAL SUR	CATE)	
NOTICE OF INTENTION TO DRILL	SUBSEQUE SUBSEQUE SUBSEQUE SUBSEQUE SUBSEQUE SUBSEQUE SUBSEQUE SUBSEQUE SUBSEQUE	NT REPORT OF WATER SHUT-OFF NT REPORT OF SHOOTING OR ACIDIZING. NT REPORT OF ALTERING CASING NT REPORT OF RE-DRILLING OR REPAIR NT REPORT OF ABANDONMENT NT REPORT OF ABANDONMENT	
A. L. serthein	ft. from. [S] line ar	March 6, March 6, hd650 ft. from (E) Ind650 line of NMPN (Meridian) Kew Mexice (State or Territory)	, 19 63 sec. 34

The elevation of the derrick floor above sea level is 3543 ft. RDE

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

This well was recompleted June 5, 1959, as a shut-in gas well. On PT well flowed 357 MCFPD 16 hrs. M/64" eh. TPF 309, CPT 410,. Due to isolated location and limited producing experialities of well, a market has and cannot be obtained. We propose to abandon as followers Spot 25 SX. example plug from PSD 9631 to 9240'(Perforations 9MA2-9458); Out and pall 4-1/2" easing from approx. 3965'. Spot 25 SX. pluge at following intervals, 3200-6100, 6700-6600, 5000-4900, 3000-2900 (in and out of 9-5/8" casing stub - 9-5/8" Merbe-next and palled from approx 2952'); 1300-1200; 750-650 (in and out of 13-3/8" OSA 760'); 10 SK. at surface with PXA marker. All intervals to be filled with heavy mud laden field. Glean and level location to its natural contour.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.			
	Pan American Petroleum Corpor		
Address	Post Office Box 68		
	Hobbs, New Mexico	ByBA	
		Title Area Superintendent	

Λ