

N.

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

WELL RECORD

Mail to Oil Conservation Commission, Santa Fe, New Mexico, or its proper agent not more than twenty days after completion of well. Follow instructions in the Rules and Regulations of the Commission. Indicate questionable data by following it with (?). SUBMIT IN TRIPLICATE.

							0

AREA 640 ACRES
LOCATE WELL CORRECTLY

Harvey E. Yates Company or Operator J. W. Jones ET AL - State Lease

Well No. 1 in N2/S2 of Sec. 32, T. 19
R. 27, N. M. P. M., Wildcat Field, Bddy County.

Well is 3630 feet south of the North line and 990 feet west of the East line of Sec. 32

If State land the oil and gas lease is No. B - 9969 Assignment No. 2

If patented land the owner is _____, Address _____

If Government land the permittee is _____, Address _____

The Lessee is Harvey E. Yates, 314 Becker Building,, Address Artesia, New Mexico

Drilling commenced Nov. 29, 1950 Drilling was completed Jan. 15, 1951

Name of drilling contractor _____, Address _____

Elevation above sea level at top of casing _____ feet.

The information given is to be kept confidential until _____ 19____.

OIL SANDS OR ZONES

No. 1, from 435 to 452 No. 4, from 740 to 746

No. 2, from 470 to 472 No. 5, from _____ to _____

No. 3, from 484 to 490 No. 6, from _____ to _____

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from No Water to _____ feet.

No. 2, from _____ to _____ feet.

No. 3, from _____ to _____ feet.

No. 4, from _____ to _____ feet.

CASING RECORD

SIZE	WEIGHT PER FOOT	THREADS PER INCH	MAKE	AMOUNT	KIND OF SHOE	CUT & FILLED FROM	PERFORATED FROM	TO	PURPOSE
No Casing									

MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
No Casing						

PLUGS AND ADAPTERS

Heaving plug—Material _____ Length _____ Depth Set _____

Adapters—Material _____ Size _____

RECORD OF SHOOTING OR CHEMICAL TREATMENT

SIZE	SHELL USED	EXPLOSIVE OR CHEMICAL USED	QUANTITY	DATE	DEPTH SHOT OR TREATED	DEPTH CLEANED OUT
None						

Results of shooting or chemical treatment _____

RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto.

TOOLS USED

Rotary tools were used from _____ feet to _____ feet, and from _____ feet to _____ feet.

Cable tools were used from _____ feet to _____ feet, and from _____ feet to _____ feet.

0

PRODUCTION

Put to producing _____, 19____

The production of the first 24 hours was _____ barrels of fluid of which _____ % was oil; _____ % emulsion; _____ % water; and _____ % sediment. Gravity, Be _____

If gas well, cu. ft. per 24 hours _____ Gallons gasoline per 1,000 cu. ft. of gas _____

Rock pressure, lbs. per sq. in. _____

EMPLOYEES

_____, Driller _____, Driller

W. P. Black, Driller _____, Driller

C. L. Bowen, _____, Driller _____

FORMATION RECORD ON OTHER SIDE

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

Place Artesia, New Mexico Date September 5, 1951

Name _____

Position Agent

Representing Harvey E. Yates Company or Operator.

Address 314 Becker Bldg., Artesia, N.M.

FORMATION RECORD

FROM	TO	THICKNESS IN FEET	FORMATION
	20	20	Lime
40	115	95	Lime & Gyp
115	140	25	Shale & Anhydrite
140	170	30	Anhydrite
170	180	10	Lime
180	215	35	Lime & Brown Shale
215	255	40	Brown Shale
255	257	2	Brown Lime
257	262	5	Black Shale
262	278	16	Lime
278	311	33	Brown & Grey Lime
311	335	24	Red Bed
335	357	22	Gray Lime
357	365	8	Brown Lime
365	386	21	Anhydrite
386	395	9	Grey Lime
395	425	30	Anhydrite
425	435	10	Lime
435	452	17	Lime
452	472	20	Brown Lime
472	495	23	Brown Lime
495	505	15	Sandy Lime
505	520	15	Lime
520	525	5	Red Sand
525	540	15	Lime & Anhydrite
540	558	18	Lime
558	570	12	Lime
570	597	27	Lime
597	690	93	Pink Lime
690	715	25	Lime
715	732	17	Red Sand
732	740	8	Pink Lime
740	746	6	Grey Lime
746	1026 T.D.	280	Lime