

		X			

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

WELL RECORD

Mail to District Office, Oil Conservation Commission, to which Form C-101 was sent not later than twenty days after completion of well. Follow instructions in Rules and Regulations of the Commission. Submit in QUINTUPPLICATE.

AREA 640 ACRES
LOCATE WELL CORRECTLY

Stanolind Oil and Gas Company
(Company or Operator)

State "N.M."
(Lease)

Well No. 1, in SW 1/4 of NE 1/4, of Sec. 3, T19-S, R. 28-E, NMPM.

Wildcat

Pool,

e Eddy

County

Well is 1650 feet from North line and 1650 feet from East line

of Section 3. If State Land the Oil and Gas Lease No. is Unknown

Drilling Commenced 6 - 27 - 54, 19. Drilling was Completed 10 - 30 - 54, 19.

Name of Drilling Contractor Noble Drilling Company

Address Stanolind Building, Tulsa, Oklahoma

Elevation above sea level at Top of Tubing Head 3530 RDB. The information given is to be kept confidential until
Not confidential, 19.

OIL SANDS OR ZONES

No. 1, from to No. 4, from to

No. 2, from to No. 5, from to

No. 3, from to No. 6, from to

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from to feet.

No. 2, from to feet.

No. 3, from to feet.

No. 4, from to feet.

CASING RECORD

SIZE	WEIGHT PER FOOT	NEW OR USED	AMOUNT	KIND OF SHOE	CUT AND PULLED FROM	PERFORATIONS	PURPOSE
13-3/8"	36#	new	594	Float			Surface
9-5/8"	32-36#	new	2446	Float			Salt String
5-1/2"	17-20#	new	11138	Float			Oil String

MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
17-1/2	13/3/8	607	550 sx	Howco Plug		
12-1/4	9-5/8	2460	300 sx	Howco Plug		
7-7/8	5-1/2	11150	175 sx	Howco Plug		

RECORD OF PRODUCTION AND STIMULATION

(Record the Process used, No. of Qts. or Gals. used, interval treated or shot.)

Plugged & Abandoned (See reverse side)

Result of Production Stimulation

Depth Cleaned Out

WORD OF DRILL-STEM AND SPECIAL TEST

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto

TOOLS USED

Rotary tools were used from 0 feet to 11442 feet, and from feet to feet.
Cable tools were used from feet to feet, and from feet to feet.

PRODUCTION

Put to Producing, 19

OIL WELL: The production during the first 24 hours was barrels of liquid of which % was
was oil; % was emulsion; % water; and % was sediment. A.P.I.
Gravity.

GAS WELL: The production during the first 24 hours was M.C.F. plus barrels of
liquid Hydrocarbon. Shut in Pressure lbs.

Length of Time Shut in

PLEASE INDICATE BELOW FORMATION TOPS (IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE):

Southeastern New Mexico

Northwestern New Mexico

T. Anhy	T. Devonian	T. Ojo Alamo
T. Salt	T. Silurian	T. Kirtland-Fruitland
B. Salt	T. Montoya	T. Farmington
T. Yates	T. Simpson	T. Pictured Cliffs
T. 7 Rivers	T. McKee	T. Menefee
T. Queen 1680'	T. Ellenburger	T. Point Lookout
T. Grayburg	T. Gr. Wash	T. Mancos
T. San Andres 2470'	T. Granite	T. Dakota
T. Glorieta	T. Wolfcamp 8640'	T. Morrison
T. Drinkard	T.	T. Penn
T. Tubbs	T.	T.
T. Abo	T.	T.
T. Penn 9430'	T.	T.
T. Miss 11390'	T.	T.

FORMATION RECORD

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	470	470	Sand & Red Bed				
470	607	137	Red Bed				
607	800	193	Red Bed & Anhy.				
800	1813	1013	Anhy.				
1813	2336	523	Anhy & Lime				
2336	4305	1969	Lime				
4305	4352	47	Lime & Chert				
4352	8172	3820	Lime				
8172	8205	33	Lime & Shale				
8205	9130	925	Lime				
9130	9289	159	Lime & Shale				
9289	10940	1651	Lime				
10940	11442	502	Lime, Shale, Sand				
Well Plugged & Abandoned 10/30/54							
Plugs set at:							
Depth	Cement-sax						
8620		25					
1700		25					
607		10					
Surface		25					

A 4" pipe to extend 4 foot above surface was set. Location was leveled and ground surface restored to natural contour.

ATTACH SEPARATE SHEET IF ADDITIONAL SPACE IS NEEDED

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

November 17, 1954

(Date)

Company or Operator Stanolind Oil and Gas Co.

Address Box 68, Hobbs, New Mexico

Name Ralph R. Hendrickson

Position or Title Field Superintendent