

N.

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico
TEST NO.

OT

MON?

AREA 640 ACRES
LOCATE WELL CORRECTLY

WELL RECORD

Mail to Oil Conservation Commission, Santa Fe, New Mexico, or its proper agent not more than twenty days after completion of well. Follow instructions in the Rules and Regulations of the Commission. Indicate questionable data by following it with (?). SUBMIT IN TRIPLICATE.

DUPLICATE

F. W. & Y. Oil Company

State

Company or Operator

Well No.

in

of Sec.

T.

R. 28

N. M. P. M.

Artesia

Field,

Eddy

County.

Well is 330 feet south of the North line and 1650 feet west of the East line of Sec. 10

If State land the oil and gas lease is No. 648 Assignment No.

If patented land the owner is Address

If Government land the permittee is Address

The Lessee is F. W. & Y. Oil Company Address Artesia, New Mexico

Drilling commenced February 17th, 1936 Drilling was completed March 20th, 1936

Name of drilling contractor F. W. & Y. Oil Co. Address Artesia, New Mexico

Elevation above sea level at top of casing feet.

The information given is to be kept confidential until 19

OIL SANDS OR ZONES

No. 1, from 2075 to 2080 No. 4, from to

No. 2, from to No. 5, from to

No. 3, from to No. 6, from to

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from to feet.

No. 2, from to feet.

No. 2, from to feet.

No. 4, from to feet.

CASING RECORD

SIZE	WEIGHT PER FOOT	THREADS PER INCH	MAKE	AMOUNT	KIND OF SHOE	CUT & FILLED FROM	PERFORATED FROM TO	PURPOSE
8 Inch Casing				570 Feet.				

MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED

PLUGS AND ADAPTERS

Heaving plug—Material Length Depth Set

Adapters—Material Size

RECORD OF SHOOTING OR CHEMICAL TREATMENT

SIZE	SHELL USED	EXPLOSIVE OR CHEMICAL USED	QUANTITY	DATE	DEPTH SHOT OR TREATED	DEPTH CLEANED OUT
March 22, 1936	Shot well	with 150 quarts of Nitro-Glycerin	from 2075 ft to 2115 ft.			

Results of shooting or chemical treatment

RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto.

TOOLS USED

Rotary tools were used from feet to feet, and from feet to feet

Cable tools were used from feet to feet, and from feet to feet

PRODUCTION

Put to producing, 19

The production of the first 24 hours was barrels of fluid of which % was oil; %

emulsion; % water; and % sediment. Gravity, Be

If gas well, cu. ft. per 24 hours Gallons gasoline per 1,000 cu. ft. of gas

Rock pressure, lbs. per sq. in.

EMPLOYEES

W. N. Welch, Driller

J. W. Kennedy, Driller

FORMATION RECORD ON OTHER SIDE

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

Subscribed and sworn to before me this 15th

day of April, 1936

Notary Public.

Artesia, New Mexico, April 15, 1936.

Name G. S. Welch

Position President

Representing F. W. & Y. Oil Company

Company or Operator

My Commission expires January 27, 1938.

Address Artesia, New Mexico

DUPLICATE

FORMATION RECORD

FROM	TO	FORMATION
0	12	Gyp
12	165	Red Sand
165	180	Gyp
180	195	Red Beds
195	217	Gyp
217	230	Red Gumbo
230	235	Red Bed
235	240	Gyp and Red Mud
240	400	Gyp
400	406	Red Mud
406	563	Salt
563	570	Anhydrite
570	810	Anhydrite and Gyp
810	835	Gyp and Red Shale
835	855	Gyp and Anhydrite
855	885	Gyp and Red Shale
885	905	Anhydrite
905	915	Red Mud and Red Shale
915	955	Gyp and Anhydrite
955	970	Red Mud
970	1000	Gyp and Anhydrite
1000	1005	Red Shale
1005	1090	Gyp and Anhydrite
1090	1100	Red Sand
1100	1205	Gyp and Anhydrite
1205	1390	Lime
1390	1400	Red Sandy Shale
1400	1440	Lime
1440	1475	Anhydrite and Red Shale
1475	1545	Lime
1545	1605	Anhydrite
1605	1616	Lime
1616	1650	Red Sand Hard
1650	1675	Anhydrite and Red Shale
1675	1810	Anhydrite
1810	1820	Sharp Sandy Lime
1820	1830	Lime
1830	1850	Sand
1850	1895	Anhydrite
1895	1925	Lime
1925	1935	Anhydrite
1935	2075	Lime
2075	2080	Soft Lime--Gas and Oil
2080	2095	Lime
2095	2115	Sandy Lime
2115	2149	Lime
2149		TOTAL DEPTH