

N

## NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

## WELL RECORD

Mail to Oil Conservation Commission, Santa Fe, New Mexico, or its proper agent not more than twenty days after completion of well. Follow instructions in the Rules and Regulations of the Commission. Indicate questionable data by following it with (?). SUBMIT IN TRIPPLICATE.

AREA 640 ACRES  
LOCATE WELL CORRECTLY

F. W. & Y. Oil Company Artesia, New Mexico  
Company or Operator Address  
State        Well No. 69 in SW SE of Sec. 10, T. 19  
Lease  
R. 28 N. M. P. M., Artesia Field, Eddy County.  
Well is        feet south of the North line and        feet west of the East line of         
If State land the oil and gas lease is No. 648 Assignment No.         
If patented land the owner is       , Address         
If Government land the permittee is       , Address         
The Lessee is F. W. & Y. Oil Company, Address Artesia, New Mexico  
Drilling commenced November 10 19 33 Drilling was completed April 13 19 34  
Name of drilling contractor Company tools, Address         
Elevation above sea level at top of casing        feet.  
The information given is to be kept confidential until        19       

## OIL SANDS OR ZONES

No. 1, from        to        No. 4, from        to         
No. 2, from        to        No. 5, from        to         
No. 3, from        to        No. 6, from        to       

## IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from        to        feet.         
No. 2, from        to        feet.         
No. 3, from        to        feet.         
No. 4, from        to        feet.       

## CASING RECORD

SIZE	WEIGHT PER FOOT	THREADS PER INCH	MAKE	AMOUNT	KIND OF SHOE	CUT & FILLED FROM	PERFORATED		PURPOSE
							FROM	TO	
10"				270'					
8 1/4"				610'					

## MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED

## PLUGS AND ADAPTERS

Heaving plug—Material        Length        Depth Set         
Adapters—Material        Size       

## RECORD OF SHOOTING OR CHEMICAL TREATMENT

SIZE	SHELL USED	EXPLOSIVE OR CHEMICAL USED	QUANTITY	DATE	DEPTH SHOT OR TREATED	DEPTH CLEANED OUT

Results of shooting or chemical treatment       

## RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto.

## TOOLS USED

Rotary tools were used from        feet to        feet, and from        feet to        feet  
Cable tools were used from surface feet to 2180 feet, and from        feet to        feet

## PRODUCTION

Put to producing        19         
The production of the first 24 hours was        barrels of fluid of which        % was oil;        %  
emulsion;        % water; and        % sediment. Gravity, Be         
If gas well, cu. ft. per 24 hours        Gallons gasoline per 1,000 cu. ft. of gas         
Rock pressure, lbs. per sq. in.       

## EMPLOYEES

W. N. Welch, Driller Frank Tigner, Driller  
A. F. Phillips, Driller J. W. Kennedy, Driller

## FORMATION RECORD ON OTHER SIDE

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

Subscribed and sworn to before me this 1stday of May, 19 34

SEAL

H. W. Glady

Notary Public

My Commission expires January 27, 1938

Place

Date

Name V. S. WelchPosition PresidentRepresenting F. W. & Y. Oil Company  
Company or OperatorAddress Artesia, New Mexico

May 17, 1934 Approved by J. D. Hunter

# FORMATION RECORD

FROM	TO	THICKNESS IN FEET	FORMATION
0	20		Gyp
20	120		Red sand
120	132		Gyp
132	215		Red sand
215	240		Gyp
240	320		Red mud
320	345		Gumbo
345	420		Gyp and red beds
420	435		Anhy
435	630		Salt
630	1120		Anhy
1120	1425		Lime
1425	1430		Red sandy shale
1430	1625		Lime
1625	1700		Red sand
1700	1753		Lime
1753	1814		Red shale
1814	1830		Sand
1830	1855		Lime and sand
1855	1882		Anhy and red shale
1882	2065		Lime
2065	2106		Dark gray sand
2106	2123		Brown lime
2123	2159		Gray sand
2159	2180		Gray lime
2180			Total depth