

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

2040 Pacheco St.
Santa Fe, NM 87505

WELL API NO.
30-015-02216

Indicate Type of Lease
STATE ☒ FEE ☐

State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)	
Type of Well: OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input checked="" type="checkbox"/> WIW	Lease Name or Unit Agreement Name East Millman Unit
Name of Operator SDX Resources, Inc.	Well No. 160
Address of Operator PO Box 5061, Midland, TX 79704	Pool name or Wildcat Millman Yts-7R (46555)
Well Location Unit Letter <u>K</u> <u>1980</u> Feet From The <u>South</u> Line and <u>1980</u> Feet From The <u>West</u> Line Section <u>11</u> Township <u>19S</u> Range <u>28E</u> NMPM <u>Eddy</u> County	
Elevation (Show whether DF, RKB, RT, GR, etc.)	

11

Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☒
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐
CASING TEST AND CEMENT JOB ☐
OTHER: ☐

Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

P&A Proposal:

Set CIBP @ 1700' & cap w/10 sx. TOC @ 1564'.

TIH & spot 25 sx plug from 1160 - 1060'

Spot 25 sx plug across surface shoe 342' to surface * 25 sx cement Plug 342' - 292' TAH

Install marker



* Bunge gel between all cement Plugs.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

Chris Morgan

TITLE Engineer

DATE 02-10-00

TYPE OR PRINT NAME

TELEPHONE NO.

(This space for State Use)

APPROVED BY

Mike Steelfield

TITLE Field Rep. II

DATE 2/24/2000

CONDITIONS OF APPROVAL, IF ANY:

* Notify NMACO to witness Plugging Operations.

EMU # 160
1980 FSL & 1980 FWL
Sec. 11 T19S R28E
Edy Co., N.M.

Existing Condition:

11" hole to 342' with 342' of 8-5/8" csg cemented with 100 sxs. (TOC calculared at surface)

6-3/4" hole to 2245' with 2245' of 4-1/2" casing cemented with 100 sxs. (TOC 610'by log)

Squeezed holes 353-384 (4 times with a total of 525 sxs) Circulated cement to surface

Perfs: 1810-2234.

Formation Tops: Seven Rivers: 1110'
 Queen: 1664'
 Grayburg: 2010'

P&A Proposal:

- 1.) Set CIBP at 1700' and cap with 10 sxs. Toc at 1564'
- 2.) TIH and spot 25 sx. Plug from 1160-1060'.
- 3.) Spot 25 sx plug across surface shoe 342' to surface.
- 4.) Install marker.