

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

OIL CONSERVATION DIVISION
P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-73

NO. OF COPIES RECEIVED	3
DISTRIBUTION	
SANTA FE	/
FILE	/
U.S.G.S.	
LAND OFFICE	
OPERATOR	/

JUN 01 1981

O. C. D.
ARTESIA, OFFICE

5a. Indicate Type of Lease State ☐ Fee ☐
5. State Oil & Gas Lease No. LC-069107

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐	7. Unit Agreement Name East Millman Pool Ut TR 6
2. Name of Operator SUN OIL COMPANY-MIDLAND-229445	8. Farm or Lease Name
3. Address of Operator P.O. Box 1861 Midland, Texas 79702	9. Well No. 4
4. Location of Well UNIT LETTER A 660 FEET FROM THE North LINE A. 990 FEET FROM THE East LINE, SECTION 13 TOWNSHIP 19S RANGE 28E N.M.P.M.	10. Field and Pool, or Wildcat Millman (Q-G) East
15. Elevation (Show whether DF, RT, GR, etc.)	12. County Eddy

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐	PLUG AND ABANDON ☐	REMEDIAL WORK ☐	ALTERING CASING ☐
TEMPORARILY ABANDON ☐	CHANGE PLANS ☐	COMMENCE DRILLING OPERATIONS ☐	PLUG AND ABANDONMENT ☐
PULL OR ALTER CASING ☐	OTHER ☒ Convert to water injection	CASING TEST AND CEMENT JOB ☐	OTHER ☐

17. Describe the Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

MIRU. Pull rods & pump install BOP. Tag btm & strap out of hole w/2 3/8" tbgr. GIH & clean out to 2285' TD.
Perf 2249-1690', 1 JSP2F, 59 holes. RIH w/cup straddle pkr on 2 7/8" WS, acidize each perforated interval w/250 gals 15% NEHCL. POH w/pkr.
RIH w/pkr to 2285' circ hole clean, PU & set pkr @1600'. Swab well back. POH w/pkr.
RIH w/5 1/2" pkr, nickel plated, set @2005'. POH w/2 7/8" WS. RIH w/2 1/16" IJ IPC tbgr. w/bevelled collars, w/5 1/2" dual hydraulic pkr & 15 jts 2 1/16" IJ IPC & externally FG wrapped tbgr. straight pull overshot for OSTD below pkr. Set dual hydraulic pkr @1600+.
Hang long string in dual well head. RIH w/nickel plated nipple, 1 1/4" IJ 4' pup jt on 2 1/16" IPC tbgr w/bevelled collars. Circ annulus w/pkr fluid.
Latch short string into upper pkr. Hang upper tbgr in slips in dual well head.
Install injection assembly.
Put on injection @max rate 200 BWPD & max TP 900#.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Series Williams TITLE Sr. Accounting Assistant DATE 5-27-81
APPROVED BY W. A. Gressett TITLE SUPERVISOR, DISTRICT 14 DATE JUN 02 1981
CONDITIONS OF APPROVAL, IF ANY: