

OIL CONSERVATION DIVISION

P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	/
FILE	/
U.S.G.S.	
LAND OFFICE	
OPERATOR	/

RECEIVED

SEP 14 1981

O. C. D.

5a. Indicate Type of Lease
State ☐ Fee ☐
5. State Oil & Gas Lease No.
LC-069107

SUNDRY NOTICES AND REPORTS ON WELLS ARTESIA, OFFICE
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐	7. Unit Agreement Name
2. Name of Operator	East Millman Pool Ut TR 6
3. Address of Operator	8. Farm or Lease Name
P.O. Box 1861, Midland, TX 79702	9. Well No.
4. Location of well	4
UNIT LETTER A 660 FEET FROM THE North LINE AND 990 FEET FROM East LINE, SECTION 13 TOWNSHIP 19S RANGE 28E N.M.P.M.	10. Field and Pool, or Wildcat
	Millman (O-G) East
15. Elevation (Show whether DF, RT, GR, etc.)	12. County
	Eddy

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐	PLUG AND ABANDON ☐	REMEDIAL WORK ☐	ALTERING CASING ☐
TEMPORARILY ABANDON ☐	CHANGE PLANS ☐	COMMENCE DRILLING OPNS. ☐	PLUG AND ABANDON NEW ☐
PULL OR ALTER CASING ☐	OTHER ☐	CASING TEST AND CEMENT JOB ☐	OTHER ☒ Convert to water injection

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

MIRU DA&S POH w/rods & pump, attempt circ well w/100 BLW (NU BOP) lower 2 3/8 tbg tag fill @2193, 92' fill, POH w/2 3/8 tbg w/pmpg, set up.
RIH w/2 7/8 HYD bailer & 2 7/8 W.S., tag & Cln out 2193-2213, bailer lost surge, POH rec SD, iron sulfide & bail sealers, reran bailer cln out 2213-2235 (22') lost surge on bailer, POH rec same as 1st run/ cellar caved in, ran 2 7/8 tbg open end out derrick in hole to set steel mat.
POH w/2 7/8 tbg/Ran 4 3/4 RB, hydrostatic bailer and 2 7/8 tbg, tag fill 2220, 15' fill overnite, clean out 2220-36, POH, bit plugged w/ball sealers/ran notched collar and hydro bailer on 2 7/8 tbg, clean out 2236-2285 PBD.
Go WL attempt perf, unable to get below fill @ 2244, RIH w/4 3/4 bit 2 7/8 hydro-bailer, 2 7/8 tbg tag and cln out fill 2244-2285, PU to 1500.
Lower 4 3/4 bit, tag TD 2285, POH w/4 3/4 bit & 2 7/8 hydro bailer, Go WL perf queen - 1976-80, 1987-91, Grayburg 1690-94, 1714-18, 1812-16, 1868-74, 1902-06, 1920,24,1947. 51 - 1976-80, 1987-91, 2026-30, 2056-58, 2068-72, 2082-86, 2100-04, 2119-23, 2190-94, 2249-53. w/4" OD densi-jet 19, 19 gm .48 EH select fire gun, by lane wells radio activity log (dated 3-9-59) RIH w/5 1/2 baker RBP & FB pkr, 2 7/8 tbg. 1300'
Finish in hole w/ 5 1/2 baker RBP & FB pkr, 2 7/8 W.S. set RBP 2255 Howco selective acidize perfs w/250 gal 15% NEHCL in each perf interval.

Continued on back --

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Dee Ann Kemp TITLE Accounting Assistant DATE 9-8-81

APPROVED BY Mike Williams TITLE OIL AND GAS INSPECTOR DATE SEP 16 1981

CONDITIONS OF APPROVAL, IF ANY: