

Submit 3 Copies to Appropriate

District Office

DISTRICT I

1625 n. French Dr., Hobbs, NM 88240

DISTRICT II

811 South First, Artesia, NM 88210

DISTRICT III

1000 Rio Brazos Rd., Aztec, NM 87410

DISTRICT IV

2040 S. Pacheco, Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

OIL CONSERVATION DIVISION

2040 South Pacheco
Santa Fe, NM 87505

RECEIVED
OCD - ARTESIA

Form C-103

Revised March 25, 1999

WELL API NO.

30-015-02300

5. Indicate Type of Lease

STATE ☒ FEE ☐

6. State Oil & Gas Lease No.

7. Lease Name or Unit Agreement Name:

State A

8. Well No.

1

9. Pool name or Wildcat Millman;

Yates-SR-QN-GB-SA, East

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS)

1. Type of Well:

Oil Well ☐ Gas Well ☐ Other ☐

2. Name of Operator

Louis Dreyfus Natural Gas Corp.

3. Address of Operator

14000 Quail Springs Parkway - Suite 600 - Oklahoma City, OK 73134

4. Well Location

Unit letter F; 1980' feet from the North line and 1980' feet from the West line.

Section 24 Township 19S Range 28E NMPM Eddy County

10. Elevation (Show whether DR, RKB, RT, Gr, etc.)

3354'

11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☒

TEMPORARILY ABANDON ☐ CHANGE PLANS ☐

PULL OR ALTER CASING ☐ MULTIPLE COMPLETION ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐ PLUG AND

CASING TEST AND CEMENT JOB ☐ ABANDONMENT ☐

OTHER: ☐

12. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

1. Set CIBP @ 2,075' cement w/ ³ sx cement.

2. 30 sx plug @ ~~850'~~ Perf csy @ 840' - Squeeze 100' of Cmt inside & outside csy. - Tag (940'-840')

3. 50 sx plug @ ~~327-127'~~ Perf. csy @ 348' - Squeeze 100' of Cmt. inside csy & outside csy - Tag (348'-327')

4. 30 sx plug @ ~~3'-33'~~ Perf. csy @ 60' - Circ. Cmt. inside & outside csy 0-60'

5. Cap well, cut anchors, clean location.

Install Dry hole marker

Salt gel mud consisting of 10#

Brine W/25# of gel per bbl

must be placed between each plug

Notify OCD 24 hrs. prior to any work done

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Carla Christian TITLE Regulatory Technician DATE 02/19/02

Type or print name Carla Christian

Telephone No. 405-749-5263

(This space for State use)

APPROVED BY [Signature] TITLE Field Rep ID DATE MAR 1 2002

Conditions of approval, if any: