7-

## OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

<u>بان</u>

Sumbit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below.

REPORT ON BEGINNING RILLING OPERA-	REPORT ON REPAIR	RING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL	REPORT ON PULLIN		
REPORT ON RESULT OF TEST OF CASING SHUT-OFF	REPORT ON DEEPE	NING WELL	
REPORT ON RESULT OF PLUGGING OF WELL	x /		
			<del></del>
	Artesia, New Mexico		1, 1950
OIL CONSERVATION COMMISSION, SANTA FE, NEW MEXICO. Gentlemen:	Date ·	Place	
Following is a report on the work done and the results o	btained under the heading no	ted above at the	
Stanely L. Jones. Inc.	Powell		
Company or Operator	Lease	_	
NE NEof Sec. 10	, T <u>19 S</u> , R.	<del>29 E</del> , 1	V. M. P. M.,
S. Turkey Track Field, Eddy			County.
The dates of this work were as follows:	shwerv 1 and 2		
Notice of intention to do the work with was not) sub	-		
and approval of the proposed plan wax (was not) obt	aineu. (Closs out incorrect w	orus. y	
Plugged back to top of pay, 5 sacks from 1050 to 1020 with cement them 300 to surface with mid them 5 sacks	m <b>from 1</b> 020' to 320' w	with mud. $320-3$	50 with mud
Plugged back to top of pay, 5 sacks from 1050 to 1020 with cement them 300 to surface with mud then 5 sack	m <b>from 1</b> 020' to 320' w	with mud. $320-3$	50 with mud CC' cement
300' to surface with mud then 5 sach	m from 1020' to 320' we ke coment and 3"-8' pi	rith mud. 320-3 pe for marker.	CC! cement
from 1050° to 1020° with cement them 300° to surface with mud then 5 sach	m from 1020' to 320' m ks cament and 3"-8' pi  Stanley L. Jone Company	pe for marker.	CC! cement Title
7rom 1050 to 1020 with cement them 300 to surface with mud then 5 sach  Vitnessed by Stanley L. Jones	m from 1020' to 320' we ke coment and 3"-8' pi	pe for marker.	CC! cement Title
Vitnessed by Stanley I. Jones Name  Subscribed and sworn before me this 17th	Stanley L. Jone Company  I hereby swear or affirm is true and correct.	pe for marker.	CC! cement Title
Witnessed by Stanley I. Jones Name  Subscribed and sworn before me this 17th  day of February 1950	Etanley L. Jone Company  I hereby swear or affirm is true and correct  Name	pe for marker.	CC! cement
Witnessed by Stanley I. Jones Name  Subscribed and sworn before me this 17th	Etanley L. Jone Company  I hereby swear or affirm is true and correct  Name  Position  Representing  Stenley  Stenley  Stenley  Programment  Programment  Programment  Programment  Programment  Programment  Stenley  Stenley  Stenley  Stenley  Stenley  Stenley  Representing	pe for marker.  s, Inc.  that the information	CC! cement
Witnessed by Stanley I. Jones Name  Subscribed and sworn before me this 17th  day of February 19-50	Etanley L. Jone Company  I hereby swear or affirm is true and correct  Name  Position  Representing  Stanley  Company	pe for marker.  s, Inc.  that the information  sident	Corent Title given above
Witnessed by Stanley I. Jones Name  Subscribed and sworn before me this 17th  day of February , 19 50	Etanley L. Jone Company  I hereby swear or affirm is true and correct  Name  Position  Representing  Stanley  Company	pe for marker.  Inc.  that the information  sident  y I. Jones, Inc.  y or Operator  rtesia, New Mex	Corent Title given above