

N.

## NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico


AREA 640 ACRES  
LOCATE WELL CORRECTLY

## WELL RECORD

Mail to Oil Conservation Commission, Santa Fe, New Mexico, or its proper agent not more than twenty days after completion of well. Follow instructions in the Rules and Regulations of the Commission. Indicate questionable data by following it with (?). SUBMIT IN TRIPLICATE.

Jones &amp; Watkins

State

Well No. 4 Company or Operator N. M. P. M. Lease 19  
in NE 1/4 of Sec. 16, T. 19S, R. 29E  
N. M. P. M. S. Seven Rivers-Turkey Field, Eddy County.  
Well is 330 feet south of the North line and 330 feet west of the East line of Sec. 16, T 19S, R 29E  
If State land the oil and gas lease is No. \_\_\_\_\_ Assignment No. \_\_\_\_\_  
If patented land the owner is \_\_\_\_\_ Address \_\_\_\_\_  
If Government land the permittee is \_\_\_\_\_ Address \_\_\_\_\_  
The Lessee is \_\_\_\_\_ Address \_\_\_\_\_  
Drilling commenced January 11 1951 Drilling was completed February 17 1951  
Name of drilling contractor Brewer Drilling Company Address Artesia, New Mexico  
Elevation above sea level at top of casing \_\_\_\_\_ feet.  
The information given is to be kept confidential until \_\_\_\_\_ 19\_\_\_\_

## OIL SANDS OR ZONES

No. 1, from 1485 to 1505 No. 4, from \_\_\_\_\_ to \_\_\_\_\_  
No. 2, from 1535 to 1569 No. 5, from \_\_\_\_\_ to \_\_\_\_\_  
No. 3, from 2141 to 2200 No. 6, from \_\_\_\_\_ to \_\_\_\_\_

## IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from 1713 to 1717 feet.  
No. 2, from \_\_\_\_\_ to \_\_\_\_\_ feet.  
No. 3, from \_\_\_\_\_ to \_\_\_\_\_ feet.  
No. 4, from \_\_\_\_\_ to \_\_\_\_\_ feet.

## CASING RECORD

SIZE	WEIGHT PER FOOT	THREADS PER INCH	MAKE	AMOUNT	KIND OF SHOE	CUT & FILLED FROM	PERFORATED FROM TO	PURPOSE
<u>8 1/2"</u>				<u>1483'</u>				
<u>7 7/8"</u>				<u>2086' 6"</u>				

## MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
	<u>8 1/2"</u>	<u>1483</u>	<u>25</u>	<u>Halliburton</u>		
	<u>7 7/8"</u>	<u>2087</u>	<u>50</u>		<u>10.0 and</u>	<u>15 sacks</u>

## PLUGS AND ADAPTERS

Heaving plug—Material \_\_\_\_\_ Length \_\_\_\_\_ Depth Set \_\_\_\_\_  
Adapters—Material \_\_\_\_\_ Size \_\_\_\_\_

## RECORD OF SHOOTING OR CHEMICAL TREATMENT

SIZE	SHELL USED	EXPLOSIVE OR CHEMICAL USED	QUANTITY	DATE	DEPTH SHOT OR TREATED	DEPTH CLEANED OUT
<u>5"</u>		<u>S.O.N.E.</u>	<u>27 qts</u>	<u>2-17-51</u>	<u>2140-2203</u>	<u>2203</u>

Results of shooting or ~~chemical treatment~~ 1 bbl. per hour to 12 bbls. per hour.

## RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto.

## TOOLS USED

Rotary tools were used from \_\_\_\_\_ feet to \_\_\_\_\_ feet, and from \_\_\_\_\_ feet to \_\_\_\_\_ feet.  
Cable tools were used from 0 feet to 2211 feet, and from \_\_\_\_\_ feet to \_\_\_\_\_ feet.

## PRODUCTION

Put to producing February 10 1951  
The production of the first 24 hours was 150 barrels of fluid of which 100 % was oil; \_\_\_\_\_ % emulsion; \_\_\_\_\_ % water; and \_\_\_\_\_ % sediment. Gravity, Be 37  
If gas well, cu. ft. per 24 hours \_\_\_\_\_ Gallons gasoline per 1,000 cu. ft. of gas \_\_\_\_\_  
Rock pressure, lbs. per sq. in. \_\_\_\_\_

## EMPLOYEES

R. Eymun Driller W. C. Cox Driller  
D. B. Shira Driller W. C. Garner Driller

## FORMATION RECORD ON OTHER SIDE

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

Subscribed and sworn to before me this \_\_\_\_\_

day of February, 19 51Erma H. Williams  
Notary PublicMy Commission expires February 19, 1952Artesia, New Mexico 2-24-51  
Place DateName Stanley JonesPosition PartnerRepresenting Jones & Watkins  
Company or Operator.Address Box 464, Artesia, New Mexico

