

NEW MEXICO OIL CONSERVATION COMMISSION
Santa Fe, New Mexico

WELL RECORD

Mail to District Office, Oil Conservation Commission, to which Form C-101 was sent not later than twenty days after completion of well. Follow instructions in Rules and Regulations of the Commission. Submit in QUINTUPLICATE. If State Land submit 6 Copies

AREA 640 ACRES
LOCATE WELL CORRECTLY

L. C. Harris, Box 6657, Roswell, N.M. Warren-State
(Company or Operator) (Lease)

Well No. 2, in NW 1/4 of NE 1/4, of Sec. 17, T. 19 S., R. 29 E., NMPM.

Undesignated Turkey Track Pool, Eddy County.

Well is 330 feet from North line and 2310 feet from East line of Section 17. If State Land the Oil and Gas Lease No. is E-1526.

Drilling Commenced Sept. 2, 1957, 19. Drilling was Completed Oct. 11, 1957, 19.

Name of Drilling Contractor. Roach & Shepard

Address. Artesia, N.M.

Elevation above sea level at Top of Tubing Head 3374 GL. The information given is to be kept confidential until Not confidential, 19.

OIL SANDS OR ZONES

No. 1, from 2036 to 2043 No. 4, from to

No. 2, from to No. 5, from to

No. 3, from to No. 6, from to

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from 150 to 155 feet.

No. 2, from to feet.

No. 3, from to feet.

No. 4, from to feet.

CASING RECORD

SIZE	WEIGHT PER FOOT	NEW OR USED	AMOUNT	KIND OF SHOE	CUT AND PULLED FROM left in hole	PERFORATIONS	PURPOSE
8 5/8	28	used	266		hole	none	surface

MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. BAGS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
10"	8 5/8	266	none	mudded		

RECORD OF PRODUCTION AND STIMULATION

(Record the Process used, No. of Qts. or Gals. used, interval treated or shot.)

None

Result of Production Stimulation

Depth Cleaned Out

CORD OF DRILL-STEM AND SPECIAL TI

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto

TOOLS USED

Rotary tools were used from 0 feet to 2967 feet, and from feet to feet.
Cable tools were used from feet to feet, and from feet to feet.

PRODUCTION

Put to Producing, 19.

OIL WELL: The production during the first 24 hours was barrels of liquid of which % was
was oil; % was emulsion; % water; and % was sediment. A.P.I.
Gravity.

GAS WELL: The production during the first 24 hours was M.C.F. plus barrels of
liquid Hydrocarbon. Shut in Pressure lbs.

Length of Time Shut in.

PLEASE INDICATE BELOW FORMATION TOPS (IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE):

Southeastern New Mexico

Northwestern New Mexico

T. Anhy. 252 260	T. Devonian	T. Ojo Alamo
T. Salt. 430	T. Silurian	T. Kirtland-Fruitland
B. Salt. 830	T. Montoya	T. Farmington
T. Yates. 1027	T. Simpson	T. Pictured Cliffs
T. 7 Rivers. 1407	T. McKee	T. Menefee
T. Queen. 2018	T. Ellenburger	T. Point Lookout
T. Grayburg. 2355	T. Gr. Wash.	T. Mancos
T. San Andres. 2738?	T. Granite	T. Dakota
T. Glorieta	T.	T. Morrison
T. Drinkard	T.	T. Penn.
T. Tubbs	T.	T.
T. Abo	T.	T.
T. Penn.	T.	T.
T. Miss.	T.	T.

FORMATION RECORD

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	10	10	Caliche	2470	2505	35	sandy dolomite
10	40	30	sandy red beds	2505	2515	10	brown sandy dolomite
40	135	95	shale	2515	2525	10	dolomite
135	145	10	red beds	2525	2550	25	brown sandy dolomite
145	210	65	red beds and sand	2550	2603	53	dolomite
210	250	40	sand, gravel and shale	2603	2615	12	brown sandy dolomite
250	430	180	anhyd, & red beds	2615	2660	45	sand and dolomite
430	830	400	salt	2660	2670	10	dolomite
830	1425	595	anhyd	2670	2715	45	brown sandy dolomite
1425	1445	20	blk sandy shale	2715	2750	35	sand
1445	1865	420	grey lime(dolomite)	2750	2780	30	dolomite
1865	1890	25	brown lime	2780	2800	20	sand
1890	2018	128	grey lime	2800	2910	110	dolomite
2018	2075	57	red and grey sand(queen)				
2075	2180	105	dolomite	2910	2930	20	sandy dolomite
2180	2210	30	sandy dolomite	2930	2967	37	brown sandy dolomite
2210	2260	50	dolomite				
2260	2280	20	sandy dolomite				
2280	2295	15	dolomite				
2295	2330	35	sand and some dolomite				
2330	2340	10	dolomite				
2340	2358	18	sand				
2358	2430	72	dolomite				
2430	2440	10	sand				
2440	2470	30	dolomite				

ATTACH SEPARATE SHEET IF ADDITIONAL SPACE IS NEEDED

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

Oct. 15, 1957

Company c- Operator L. C. Harris
Name

Box 6657, Roswell, N.M.
Address
Position or Title