

N

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

AREA 640 ACRES
LOCATE WELL CORRECTLY

WELL RECORD

Mail to Oil Conservation Commission, Santa Fe, New Mexico, or its proper agent not more than twenty days after completion of well. Follow instructions in the Rules and Regulations of the Commission. Indicate questionable data by following it with (?). SUBMIT IN TRIPLICATE.

Henry Swift San Antonio, Texas
Company or Operator Address

State Well No. 1 in NW NE of Sec. 20, T. 19
Lease

R. 29, N. M. P. M., Wildcat Field, Eddy County.

Well is 660 feet south of the North line and 1993 feet west of the East line of section 20

If State land the oil and gas lease is No. B-256 Assignment No.

If patented land the owner is Address

If Government land the permittee is Address

The Lessee is Henry Swift Address San Antonio, Texas

Drilling commenced October 22 19 39 Drilling was completed December 6 19 39

Name of drilling contractor Jamison & Pollard Address Abilene, Texas

Elevation above sea level at top of casing 3305 feet.

The information given is to be kept confidential until 19

OIL SANDS OR ZONES

No. 1, from to No. 4, from to

No. 2, from to No. 5, from to

No. 3, from to No. 6, from to

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from 260 to 280 feet. Hole full of water

No. 2, from 1520 to 1605 feet. 4 BWPH

No. 3, from 2206 to 2215 feet. Hole full sulphur water

No. 4, from to feet.

CASING RECORD

SIZE	WEIGHT PER FOOT	THREADS PER INCH	MAKE	AMOUNT	KIND OF SHOE	CUT & FILLED FROM	PERFORATED		PURPOSE
							FROM	TO	
10"	40#	8thd	Nat'l	83'					Surface
8 1/2"	28#	8thd	Nat'l	417'					Water S.O.

MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
10"	8 1/2"	417'	50	Halliburton		

PLUGS AND ADAPTERS

Heaving plug—Material Length Depth Set

Adapters—Material Size

RECORD OF SHOOTING OR CHEMICAL TREATMENT

SIZE	SHELL USED	EXPLOSIVE OR CHEMICAL USED	QUANTITY	DATE	DEPTH SHOT OR TREATED	DEPTH CLEANED OUT

Results of shooting or chemical treatment

RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto.

TOOLS USED

Rotary tools were used from feet to feet, and from feet to feet

Cable tools were used from 0 feet to 2215 feet, and from feet to feet

PRODUCTION

Put to producing Well not productive, 19

The production of the first 24 hours was barrels of fluid of which % was oil; % emulsion; % water; and % sediment. Gravity, Be

If gas well, cu. ft. per 24 hours Gallons gasoline per 1,000 cu. ft. of gas

Rock pressure, lbs. per sq. in.

EMPLOYEES

H. T. Marshall Driller J. W. Miller Driller

Reese Porter Driller

FORMATION RECORD ON OTHER SIDE

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

Subscribed and sworn to before me this 11

Hobbs, New Mexico 1-11-40

Place Date

day of January 19 40

Name C. C. Rollard

SEAL

Position Drilling Contractor

Norma Belle
Notary Public

Representing Henry Swift

Company or Operator

My Commission expires November 20, 1943

Address San Antonio, Texas

FORMATION RECORD

FROM	TO	THICKNESS IN FEET	FORMATION
0	70		Sand
70	85		Gravel
85	90		Anhy
90	115		Sand
115	135		Anhy & sand
135	260		Red rock and anhy
260	280		Anhy, hole full water
280	360		Salt, anhy, potash.
360	680		Salt, anhy, potash
680	693		Anhy
693	856		Salt
856	935		Lime
935	940		Red rock
940	1070		Lime
1070	1093		Anhy and red rock
1093	1125		Lime and anhy
1125	1309		Anhy
1309	1332		Lime and anhy
1332	1364		Sand and anhy
1364	1475		Anhy
1475	1505		Sandy shale & anhy
1505	1875		Lime
1875	1897		Sandy shale
1897	2040		Lime
2040	2078		Sand
2078	2139		Lime
2139	2142		Sand smell of sulphur & rainbow oil
2142	2215		Lime
2215			Total depth