



(SUBMIT IN TRIPLICATE)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

Land Office Las Cruces  
Lease No. 060985  
Unit 2

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF	
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT	<input checked="" type="checkbox"/>
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL		

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

February 6, 1956

**Federal Notes**

Well No. 1 is located 640 ft. from N line and 640 ft. from E line of sec. 3

1/4 3 17 33 187N

(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)

Midland Midland New Mexico

(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is \_\_\_\_\_ ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Well was plugged as follows: 4225' to 4400' - Filled with Gellies mud, 4400' to 4390' Cement Out off water - 4390' - 4350' to 4340' Gellies mud, 4300' to 4200' Cement - 4200' to 2400' - Gellies mud, 2400' to 2300' Cement, 2400' to 1675' Gel, 1675' to 900' Cement, 900' to 700' Gellies mud, 700' to 400' Cement - 125'. This brought the cement up to 125' in the 10-3/4" surface casing, 4" line pipe cemented in top of 10-3/4" surface extending 5' above ground.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company H. E. Black

Address Box 174

Midland, Texas

By [Signature]

Title Agent