NEW MEXICO OIL CONSERVATION COMMISSION Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WELLS

Submit this report in TRIPLICATE to the District Office, Oil Conservation Commission, within 10 days after the work specified is completed. It should be signed and filed as a report on Beginning Drilling Operations, Results of test of casing shut-off, result of plugging of well, result of well repair, and other important operations, even though the work was witnessed by an agent of the Commission. See additional instructions in the Rules and Regulations of the Commission.

		II	1
REPORT ON BEGINNING DRILLING OPERATIONS	REPORT ON RESULT OF TEST OF CASING SHUT-OFF	REPORT ON REPAIRING WELL	
REPORT ON RESULT DF PLUGGING WELL	REPORT ON RECOMPLETION OPERATION	REPORT ON (Other)	
	June 20, 1953		Place)
Following is a report on the work	done and the results obtained under the heading	noted above at the	
	•	- Nowden - ME Tu	schey
(Company or Ope	rator)	(Lease)	<i>I</i>
Company Tools	, Well No	in the NE 1/4 5#-5E	of Sec. 16
	nson Pool,		
, к, кмрм.,	Pool,		County
The Dates of this work were as follows:	From June 8th tHru June 20,	1953	
YY	(was not) submitted on Form C-102 on		
office of intention to do the work (was)	(was not) submitted on Form C-102 on	(Cross out incorrect words)	, 19
nd approval of the proposed plan (was) DETAIL	(was not) obtained. LED ACCOUNT OF WORK DONE AND RESU	ULTS OBTAINED	
nd approval of the proposed plan (was) DETAIL al depth 1846' Gravel brick byered 1550' of 7" O D. Reige and cement in the top	(was not) obtained.	SULTS OBTAINED 800° to 1846°. sks of cement to withing erected regulation management to the companion outhwest Potash Co	in 180° of rker. Ly Engineer
nd approval of the proposed plan (was) DETAIL al depth 1846' Gravel brick evered 1550' of 7" O D. Redige and cement in the top	(was not) obtained. LED ACCOUNT OF WORK DONE AND RESULTING and lead wool plugged from 1 an tubing and cemented with 300 of 8* casing at the surface and	SULTS OBTAINED 800° to 1846°. sks of cement to withing erected regulation management to the companion outhwest Potash Co	in 180° of
nd approval of the proposed plan (was) DETAIL al depth 1846' Gravel brick byered 1550' of 7" O D. Relige and cement in the top	(was not) obtained. LED ACCOUNT OF WORK DONE AND RESULTING and lead wool plugged from 1 an tubing and cemented with 300 of 8* casing at the surface and	SULTS OBTAINED 800° to 1846°. sks of cement to withing erected regulation management to the companion outhwest Potash Co	in 180° of rker. Ly Engineer
nd approval of the proposed plan (was) DETAIL al depth 1846' Gravel brick byered 1550' of 7" O D. Relige and cement in the top	(was not) obtained. LED ACCOUNT OF WORK DONE AND RESULTING and lead wool plugged from 1 an tubing and cemented with 300 of 8* casing at the surface and	SULTS OBTAINED 800° to 1846°. sks of cement to withing erected regulation management to the companion outhwest Potash Co	in 180° of rker. Ly Engineer
nd approval of the proposed plan (was) DETAIL al depth 1846' Gravel brick byered 1550' of 7" O D. Reige and cement in the top	(was not) obtained. LED ACCOUNT OF WORK DONE AND RESULTING and lead wool plugged from 1 an tubing and cemented with 300 of 8* casing at the surface and	SULTS OBTAINED 800° to 1846°. sks of cement to withing erected regulation management to the companion outhwest Potash Co	in 180° of rker. Ly Engineer
DETAIL al depth 1846' Gravel brick byered 1550' of 7" O D. Redge and cement in the top gging job was done under the	(was not) obtained. LED ACCOUNT OF WORK DONE AND RESURING and lead wool plugged from 1 an tubing and cemented with 300 of 8" casing at the surface and the direction and witnessed by Scheme direction and witnes	800° to 1846°. sks of cement to withi erected regulation manuthwest Potash Compan	in 180° of rker. Ty Engineer
DETAIL al depth 1846 Gravel brid byered 1550 of 7 0 D. Ridge and cement in the top gging job was done under the second of the	(was not) obtained. LED ACCOUNT OF WORK DONE AND RESURING and lead wool plugged from 1 an tubing and cemented with 300 of 8" casing at the surface and the direction and witnessed by Scheduler and Witnessed by	800° to 1846°. sks of cement to withing erected regulation management to the companion outhwest Potash Companion of the com	in 180° of rker. Ty Engineer
DETAIL al depth 1846 Gravel brickwered 1550 of 7 0 D. Reige and cement in the top gging job was done under it	(was not) obtained. LED ACCOUNT OF WORK DONE AND RESURING and lead wool plugged from 1 an tubing and cemented with 300 of 8" casing at the surface and the direction and witnessed by Scheme direction and witnessed by Scheme Company) I hereby certify the	SOO' to 1846'. sks of cement to within erected regulation management to the companion outhwest Potash Companion (Title) Co. Geologie (Title)	in 180° of rker. ly Engineer
DETAIL al depth 1846' Gravel brickwered 1550' of 7" O D. Redge and cement in the top gging job was done under the second of the	(was not) obtained. LED ACCOUNT OF WORK DONE AND RESURING and lead wool plugged from 1 an tubing and cemented with 300 of 8" casing at the surface and the direction and witnessed by Scheduler (Company) Southwest Potash (Company) I hereby certify the to the best of my	SOO' to 1846'. sks of cement to within erected regulation management to the companion outhwest Potash Companion (Title) Co. Geologie (Title)	n 180° of rker. y Engineer
DETAIL al depth 1846 Gravel brickwared 1550 of 7 0 D. Relige and cement in the top gging job was done under the second of the se	(was not) obtained. LED ACCOUNT OF WORK DONE AND RESURING and lead wool plugged from 1 an tubing and cemented with 300 of 8" casing at the surface and the direction and witnessed by Scheme direction and witnessed by Scheme (Company) OMMISSION I hereby certify the to the best of my Name	SOO! to 1846'. sks of cement to within erected regulation management and companion outhwest Potash Companion (Title) (Title)	n 180° of rker. y Engineer