

NEW MEXICO OIL CONSERVATION COMMISSION
Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WELLS

Submit this report in TRIPLICATE to the District Office, Oil Conservation Commission, within 10 days after the work specified is completed. It should be signed and filed as a report on Beginning Drilling Operations, Results of test of casing shut-off, result of plugging of well, result of well repair, and other important operations, even though the work was witnessed by an agent of the Commission. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Report by Checking Below

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF PLUGGING WELL	X	REPORT ON RECOMPLETION OPERATION		REPORT ON (Other)	

April 27, 1953

(Date)

Artesia, New Mexico

(Place)

Following is a report on the work done and the results obtained under the heading noted above at the

Harvey E. Yates

(Company or Operator)

Whelan State #1

(Lease)

Harvey E. Yates

(Contractor)

Well No. 1 in the SE 1/4 NE 1/4 of Sec. 16

T. 19 S, R. 30 E, NMPM, Benson Pool, Bddy County.

The Dates of this work were as follows:

Notice of intention to do the work (was) (was not) submitted on Form C-102 on _____, 19____, (Cross out incorrect words)

and approval of the proposed plan (was) (was not) obtained.

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

2920' to 2800 gravel-150# lead wool from 2800' to 2795-Pumped five sacks cement onlead from 2795 to 2785. Mud back to 1885 and bridge at 1885 gravel back to 1840-100# leadwoal, ten sacks cement on lead. 1835' of 7" OD pipe cemented in hole, knocked off and recovered 1550'. Tubing run in hole to the top of the bridge. 500 sacks cement was pumped into the hole with 3 o/e calcium chloride. This brought the cement solid up thru the salt section into the 8" surface pipe. 405' of 8" pipe cemented in hole, knocked off and recovered 100', Cemented with fifty sacks-Tubing run back in hole and 100 more sacks cement pumped in on top other cement. Cement bridge placed at top of hole and regulation macker set- March 17, 1953.

POW

Witnessed by Mr. Reid M. Waltman Southwest Potash Co. Geologist
(Name) (Company) (Title)

Approved: OIL CONSERVATION COMMISSION

I hereby certify that the information given above is true and complete to the best of my knowledge.

Name: *Bob Clark*Position: *Business*Representing: *Harvey E. Yates*Address: *PO Box 395 Artesia, N.M.*

(Title)

(Date)

3

/

/

✓