



(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office

Lease No. **55-06767**Unit **J**

RECEIVED

JUL 12 1961

SUNDRY NOTICES AND REPORTS ON WELLS

O. C. C.
ARTESIA, OFFICE

NOTICE OF INTENTION TO DRILL.....	SUBSEQUENT REPORT OF WATER SHUT-OFF.....
NOTICE OF INTENTION TO CHANGE PLANS.....	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.....
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....	SUBSEQUENT REPORT OF ALTERING CASING.....
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.....	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR.....
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....	SUBSEQUENT REPORT OF ABANDONMENT..... <input checked="" type="checkbox"/>
NOTICE OF INTENTION TO PULL OR ALTER CASING.....	SUPPLEMENTARY WELL HISTORY.....
NOTICE OF INTENTION TO ABANDON WELL.....	

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

..... May 19, 1961

LeBow-Federal

Well No. 3 is located 1650 ft. from S line and 1900 ft. from E line of sec. 25

SW 1/4 of Sec. 25 188 305 18824

(Q. Sec. and Sec. No.) (Twp.) (Range) (Meridian)

South Benson-Yates **Eddy** **New Mexico**

(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is 3407 ft.

RECEIVED

DETAILS OF WORK

MAY 22 1961

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

U. S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

5/17-18/61 Total depth 2202' DF. Plugged well as follows:

Filled hole with 10/ mud and placed plug #1 from 2100' - 2000' with 25 sacks of regular cement, plug #2 from 1816' - 1666' with 37 sacks of regular cement, plug #3 from 675' - 525' with 55 sacks of regular cement. Cut surface casing at 424', unable to pull free, cut casing at 382' and unable to pull free. Cut 8-5/8" casing at 340' and pulled 8 joints totaling 339.58'. Circulated 10/ mud to top of cement plug at 525' and finished plugging as follows: plug #4 from 432' - 300' with 80 sacks of regular cement, plug #5 from 300' - 200' with 80 sacks of regular cement and plug #6 in top of hole with 5 sacks of regular cement. Plugged and abandoned.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company G. H. StrakeAddress 3300 Gulf BuildingHouston 2, TexasBy C. R. MoteTitle Prod. Supt.