

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPlicate
Other Attachments
verse side

Budget Bureau No. 1004-0145
Expires August 31, 1985

5. LEASE DESIGNATION AND SERIAL NO.

LC-029388-A

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Shugart "A"

9. WELL NO.

2

10. FIELD AND POOL, OR WILDCAT

Shugart 4-5F-2-B

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 10-18S-31E

12. COUNTY OR PARISH 13. STATE

Eddy

NM

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☐ GAS WELL ☒ OTHER ☐ Water Injection

2. NAME OF OPERATOR

William A. & Edward R. dson

3. ADDRESS OF OPERATOR

P.O. Box 9, Maljamar, New Mexico 88264

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below.)
At surface

1980' from south and west lines,
Sec. 10-18S-31E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GN, etc.)

3724' DF

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREATMENT

ALTERING CASING

SHOOTING OR ACIDIZING

ABANDONMENT*

(Other)

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any
proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones perti-
nent to this work.)*

On Dec. 5, 1989, this well was plugged and abandoned using the
following procedure;

Set a "cast iron" bridge plug in 5-1/2" casing at 3200', loaded
hole w/salt gel mud, spotted 60' cement (6 sks.) on top of plug, spotted
100' cement (10 sks.) from 1995' to 1895', perforated 5-1/2" casing
w/4 holes at 780', broke circulation, set a cement retainer in 5-1/2"
casing at 710', loaded hole w/fresh water, circulated cement to the sur-
face using 160 sks. class "C" cement, spotted 150' cement (15 sks.) on
top of the cement retainer, spotted 60' (6 sks.) cement at the surface.
Installed a 4" x 8' dry hole marker w/all well data.

Dec. 6, 1989, the location was cleaned of all debris.

Dec. 13, 1989, the location and road was ripped to a depth of 12"
and an earthen barricade was installed to discourage vehicular travel.

Dec. 14, 1989, the area was re-seeded w/5# alkali sacaton and 20#
four wing saltbrush. CVE was notified to remove two power poles. The
surface restoration work has been completed and the area is ready for
final inspection.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

Prod. Supt.

DATE 12-14-89

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

Approval as to plugging of the well bore,
Liaison with the Bureau until
surface restoration is completed.

*See Instructions on Reverse Side

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the
United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.