and the state of t	
Form 9-331ITED STATESSUBMIT IN TP(May 1963)(May 1963)	ICATE* Form approved.
DEPART' .IT OF THE INTERIOR (Other Instruction verse side)	on re- 5. LEASE DESIGNATION AND SERIAL N
GEOLOGICAL SURVEY	LC 047633 (a)
SUNDRY NOTICES AND REPORTS ON WELLS	6. IF INDIAN, ALLOTTEE OR TRIBE NAT
(Do not use this form for proposals to drill or to deepen or plug back to a different record	olr.
(Do not use this form for proposals to drill or to deepen or plug back to a different reserve Use "APPLICATION FOR PERMIT-" for such proposals.)	
	7. UNIT AGREEMENT NAME
WELL WELL OTHER	
2. NAME OF OPERATOR	8. FARM OR LEASE NAME
Atlantic Richfield Company	bit . Swearingen ".
3. ADDRESS OF OPERATOR	9 WELL NO. 2.
P.O. BOX 1978, ROSWELL, New Mexico 88201 4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*	4 4 3 4 4 5 5 5 5 5 5 5 5 5 5
See also space 17 below.) At surface	10. FIELD AND POOL, OR WILDCAT
	Shugart
1980' FNL & 1980' FEL (Unit Letter G)	11. SEC., T., B., M., OR BLK. AND SURVEY OR AREA
	Sec. 14, T-18S, R
14. PERMIT NO. 15. ELEVATIONS (Show whether DF, RT, GR, etc.)	12. COUNTY OF PARISH 13. STATE
3722' GR	[영화] 물 문 문 문 문 지원
16. Check Appropriate Box To Indicate Nature of Notice, Rep.	ort, or Other Data
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
TEST WATER SHUT-OFF PULL OR ALTER CASING WATER SHUT-OFF	
FRACTURE TREAT MULTIPLE COMPLETE FRACTURE TREATM	ENT ALTEBING CASING
SHOOT OR ACIDIZE ABANDON* X SHOOTING OR ACIDI	
REPAIR WELL CHANGE PLANS (Other)	
(Other) (NOTE: Repo	rt results of multiple completion on Well r Recompletion Report and Log form.)
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all nontinent details and the	
proposed work. If well is directionally drilled, give subsurface locations and measured and tr nent to this work.) *	"he vertical depths for all markage and same no-
This well was shut in on 5/28/69 when product	ion dropped to less
	ion dropped to less ed to increase pro-
This well was shut in on 5/28/69 when product than 1 BOPD. Remedial acid work on 4/69 fail duction. We now propose to P & A well as fol	ion dropped to less ed to increase pro-
This well was shut in on 5/28/69 when product than 1 BOPD. Remedial acid work on 4/69 fail duction. We now propose to P & A well as fol 1. Spot 30 sx cement in 7" casing from 3310-	ion dropped to less ed to increase pro- lows: low plan and 3180
This well was shut in on 5/28/69 when product than 1 BOPD. Remedial acid work on 4/69 fail duction. We now propose to P & A well as fol 1. Spot 30 sx cement in 7" casing from 3310- 2. Cut off and recover 7" csg from about 100	ion dropped to less ed to increase pro- lows: University to word 3180 - 1200 -
This well was shut in on 5/28/69 when product than 1 BOPD. Remedial acid work on 4/69 fail duction. We now propose to P & A well as fol 1. Spot 30 sx cement in 7" casing from 3310- 2. Cut off and recover 7" csg from about 100 3. Set cement plugs; 30 sx in & out of 7" st	ion dropped to less ed to increase pro- lows: up and building with a second 3180-1200 in an & out
This well was shut in on 5/28/69 when product than 1 BOPD. Remedial acid work on 4/69 fail duction. We now propose to P & A well as fol 1. Spot 30 sx cement in 7" casing from 3310- 2. Cut off and recover 7" csg from about 100	ion dropped to less ed to increase pro- lows: up and building with a second 3180-1200 in an & out
This well was shut in on 5/28/69 when product than 1 BOPD. Remedial acid work on 4/69 fail duction. We now propose to P & A well as fol 1. Spot 30 sx cement in 7" casing from 3310- 2. Cut off and recover 7" csg from about 100 3. Set cement plugs; 30 sx in & out of 7" st of 8-5/8" shoe @ 885' & 10 sx in top of w	ion dropped to less de la pro- los pro-
This well was shut in on 5/28/69 when product than 1 BOPD. Remedial acid work on 4/69 fail duction. We now propose to P & A well as fol 1. Spot 30 sx cement in 7" casing from 3310- 2. Cut off and recover 7" csg from about 100 3. Set cement plugs; 30 sx in & out of 7" st of 8-5/8" shoe @ 885' & 10 sx in top of w Salt gel mud will be used to spot all plugs.	ion dropped to less ed to increase pro- lows: Ut a multiplet an antiplet 3180'- 0.0 in which is an in- ub. 30. It multiplet an antiplet ub. 30. It must be an in- ell. at the stranger is an ell. at the stranger is stranger is a stranger stranger is a stranger stranger is a stranger stranger is a stranger stranger is a stranger is a stranger is a stranger is a stranger is a stranger stranger is a stranger is a strang
This well was shut in on 5/28/69 when product than 1 BOPD. Remedial acid work on 4/69 fail duction. We now propose to P & A well as fol 1. Spot 30 sx cement in 7" casing from 3310- 2. Cut off and recover 7" csg from about 100 3. Set cement plugs; 30 sx in & out of 7" st of 8-5/8" shoe @ 885' & 10 sx in top of w Salt gel mud will be used to spot all plugs. will remain intact. A dry hole marker will b	ion dropped to less ed to increase pro- lows: Ut a multiplet an antiplet 3180'- 0.0 in which is an in- ub. 30. It multiplet an antiplet ub. 30. It must be an in- ell. at the stranger is an ell. at the stranger is stranger is a stranger stranger is a stranger stranger is a stranger stranger is a stranger stranger is a stranger is a stranger is a stranger is a stranger is a stranger stranger is a stranger is a strang
This well was shut in on 5/28/69 when product than 1 BOPD. Remedial acid work on 4/69 fail duction. We now propose to P & A well as fol 1. Spot 30 sx cement in 7" casing from 3310- 2. Cut off and recover 7" csg from about 100 3. Set cement plugs; 30 sx in & out of 7" st of 8-5/8" shoe @ 885' & 10 sx in top of w Salt gel mud will be used to spot all plugs. will remain intact. A dry hole marker will b cleared & levelled.	ion dropped to less ed to increase pro- lows: Ut a multiplet an antiplet 3180'- 0.0 in which is an in- ub. 30. It multiplet an antiplet ub. 30. It must be an in- ell. at the stranger is an ell. at the stranger is stranger is a stranger stranger is a stranger stranger is a stranger stranger is a stranger stranger is a stranger is a stranger is a stranger is a stranger is a stranger stranger is a stranger is a strang
This well was shut in on 5/28/69 when product than 1 BOPD. Remedial acid work on 4/69 fail duction. We now propose to P & A well as fol 1. Spot 30 sx cement in 7" casing from 3310- 2. Cut off and recover 7" csg from about 100 3. Set cement plugs; 30 sx in & out of 7" st of 8-5/8" shoe @ 885' & 10 sx in top of w Salt gel mud will be used to spot all plugs. will remain intact. A dry hole marker will b	ion dropped to less ed to increase pro- lows: Ut a multiplet an antiplet 3180'- 0.0 in which is an in- ub. 30. It multiplet an antiplet ub. 30. It must be an in- ell. at the stranger is an ell. at the stranger is stranger is a stranger stranger is a stranger stranger is a stranger stranger is a stranger stranger is a stranger is a stranger is a stranger is a stranger is a stranger stranger is a stranger is a strang
This well was shut in on 5/28/69 when product than 1 BOPD. Remedial acid work on 4/69 fail duction. We now propose to P & A well as fol 1. Spot 30 sx cement in 7" casing from 3310- 2. Cut off and recover 7" csg from about 100 3. Set cement plugs; 30 sx in & out of 7" st of 8-5/8" shoe @ 885' & 10 sx in top of w Salt gel mud will be used to spot all plugs. will remain intact. A dry hole marker will b cleared & levelled.	ion dropped to less ed to increase pro- lows: Ut a multiplet an antiplet 3180'- 0.0 in which is an in- ub. 30. It multiplet an antiplet ub. 30. It must be an in- ell. at the stranger is an ell. at the stranger is stranger is a stranger stranger is a stranger stranger is a stranger stranger is a stranger stranger is a stranger is a stranger is a stranger is a stranger is a stranger stranger is a stranger is a strang
This well was shut in on 5/28/69 when product than 1 BOPD. Remedial acid work on 4/69 fail duction. We now propose to P & A well as fol 1. Spot 30 sx cement in 7" casing from 3310- 2. Cut off and recover 7" csg from about 100 3. Set cement plugs; 30 sx in & out of 7" st of 8-5/8" shoe @ 885' & 10 sx in top of w Salt gel mud will be used to spot all plugs. will remain intact. A dry hole marker will b cleared & levelled.	ion dropped to less ed to increase pro- lows: higher motion of all all all all all all all all all al
This well was shut in on 5/28/69 when product than 1 BOPD. Remedial acid work on 4/69 fail duction. We now propose to P & A well as fol 1. Spot 30 sx cement in 7" casing from 3310- 2. Cut off and recover 7" csg from about 100 3. Set cement plugs; 30 sx in & out of 7" st of 8-5/8" shoe @ 885' & 10 sx in top of w Salt gel mud will be used to spot all plugs. will remain intact. A dry hole marker will b cleared & levelled.	ion dropped to less ed to increase pro- lows: higher motion of all all all all all all all all all al
This well was shut in on 5/28/69 when product than 1 BOPD. Remedial acid work on 4/69 fail duction. We now propose to P & A well as fol 1. Spot 30 sx cement in 7" casing from 3310- 2. Cut off and recover 7" csg from about 100 3. Set cement plugs; 30 sx in & out of 7" st of 8-5/8" shoe @ 885' & 10 sx in top of w Salt gel mud will be used to spot all plugs. will remain intact. A dry hole marker will b cleared & levelled. RECEIVED JUN 4 1970 JUN	ion dropped to less ed to increase pro- lows: higher motion of all all all all all all all all all al
This well was shut in on 5/28/69 when product than 1 BOPD. Remedial acid work on 4/69 fail duction. We now propose to P & A well as fol 1. Spot 30 sx cement in 7" casing from 3310- 2. Cut off and recover 7" csg from about 100 3. Set cement plugs; 30 sx in & out of 7" st of 8-5/8" shoe @ 885' & 10 sx in top of w Salt gel mud will be used to spot all plugs. will remain intact. A dry hole marker will b cleared & levelled. RECEIVED JUN 4 1970 JUN 0. C. C.	ion dropped to less ed to increase pro- lows: higher motion of all all all all all all all all all al
This well was shut in on 5/28/69 when product than 1 BOPD. Remedial acid work on 4/69 fail duction. We now propose to P & A well as fol 1. Spot 30 sx cement in 7" casing from 3310- 2. Cut off and recover 7" csg from about 100 3. Set cement plugs; 30 sx in & out of 7" st of 8-5/8" shoe @ 885' & 10 sx in top of w Salt gel mud will be used to spot all plugs. will remain intact. A dry hole marker will b cleared & levelled. RECEIVED JUN 4 1970 JUN 0. C. C.	ion dropped to less ed to increase pro- lows: higher motion of all all all all all all all all all al
This well was shut in on 5/28/69 when product than 1 BOPD. Remedial acid work on 4/69 fail duction. We now propose to P & A well as fol 1. Spot 30 sx cement in 7" casing from 3310- 2. Cut off and recover 7" csg from about 100 3. Set cement plugs; 30 sx in & out of 7" st of 8-5/8" shoe @ 885' & 10 sx in top of w Salt gel mud will be used to spot all plugs. will remain intact. A dry hole marker will b cleared & levelled. RECEIVED JUN 4 1970 JUN 0. C. C. C. ARTESIA, DEFICE 18. I hereby certify that the foregoing is grue and correct STUNED	ion dropped to less ion dropped to less ed to increase pro- lows: Unated and the string also be able to work of a string of 1200 and the string string ell. also be able to an another a bout string e installed and string to some the string of the string of the string of the string e installed and the string of the string of the string of the string of the string of the string of the string of the string of string of the string of the string of the string of string of the string of the string of the string of string of the string of the string of the string of string of the string of the string of the string of string of the string of the string of the string of string of the string of the string of the string of string of the string of the string of the string of the string of string of the string of the string of the string of the string of string of the string of the str
This well was shut in on 5/28/69 when product than 1 BOPD. Remedial acid work on 4/69 fail duction. We now propose to P & A well as fol 1. Spot 30 sx cement in 7" casing from 3310- 2. Cut off and recover 7" csg from about 100 3. Set cement plugs; 30 sx in & out of 7" st of 8-5/8" shoe @ 885' & 10 sx in top of w Salt gel mud will be used to spot all plugs. will remain intact. A dry hole marker will b cleared & levelled. RECEIVED JUN 4 1970 JUN C. C. C. ARTESIA, OFFICE	ion dropped to less ion dropped to less ed to increase pro- lows: Unated and the string also be able to work of a string of 1200 and the string string ell. also be able to an another a bout string e installed and string to some the string of the string of the string of the string e installed and the string of the string of the string of the string of the string of the string of the string of the string of string of the string of the string of the string of string of the string of the string of the string of string of the string of the string of the string of string of the string of the string of the string of string of the string of the string of the string of string of the string of the string of the string of string of the string of the string of the string of the string of string of the string of the string of the string of the string of string of the string of the str
This well was shut in on 5/28/69 when product than 1 BOPD. Remedial acid work on 4/69 fail duction. We now propose to P & A well as fol 1. Spot 30 sx cement in 7" casing from 3310- 2. Cut off and recover 7" csg from about 100 3. Set cement plugs; 30 sx in & out of 7" st of 8-5/8" shoe @ 885' & 10 sx in top of w Salt gel mud will be used to spot all plugs. will remain intact. A dry hole marker will b cleared & levelled. RECEIVED JUN 4 1970 JUN 13. I hereby certify that the foregoing is grue and correct SIGNED Automotion (This space for Federal or State office use)	ion dropped to less ion dropped to less ed to increase pro- lows: Unated and the string also be able to work of a string of 1200 and the string string ell. also be able to an another a bout string e installed and string to some the string of the string of the string of the string e installed and the string of the string of the string of the string of the string of the string of the string of the string of string of the string of the string of the string of string of the string of the string of the string of string of the string of the string of the string of string of the string of the string of the string of string of the string of the string of the string of string of the string of the string of the string of string of the string of the string of the string of the string of string of the string of the string of the string of the string of string of the string of the str
This well was shut in on 5/28/69 when product than 1 BOPD. Remedial acid work on 4/69 fail duction. We now propose to P & A well as fol 1. Spot 30 sx cement in 7" casing from 3310- 2. Cut off and recover 7" csg from about 100 3. Set cement plugs; 30 sx in & out of 7" st of 8-5/8" shoe @ 885' & 10 sx in top of w Salt gel mud will be used to spot all plugs. will remain intact. A dry hole marker will b cleared & levelled. RECEIVED JUN 4 1970 JUN 13. I hereby certify that the foregoing is grue and correct SIGNED Automotion (This space for Federal or State office use)	ion dropped to less ion dropped to less ed to increase pro- lows: Unated and the string also be able to work of a string of 1200 and the string string ell. also be able to an another a bout string e installed and string to some the string of the string of the string of the string e installed and the string of the string of the string of the string of the string of the string of the string of the string of string of the string of the string of the string of string of the string of the string of the string of string of the string of the string of the string of string of the string of the string of the string of string of the string of the string of the string of string of the string of the string of the string of string of the string of the string of the string of the string of string of the string of the string of the string of the string of string of the string of the str
This well was shut in on 5/28/69 when product than 1 BOPD. Remedial acid work on 4/69 fail duction. We now propose to P & A well as fol 1. Spot 30 sx cement in 7" casing from 3310- 2. Cut off and recover 7" csg from about 100 3. Set cement plugs; 30 sx in & out of 7" st of 8-5/8" shoe @ 885' & 10 sx in top of w Salt gel mud will be used to spot all plugs. will remain intact. A dry hole marker will b cleared & levelled. RECEIVED JUN 4 1970 JUN 13. I hereby certify that the foregoing is grue and correct SIGNED Automotion (This space for Federal or State office use)	ion dropped to less ed to increase pro- lows: Una routing of the pro- lows: Una routing of the pro- lows: Una routing of the pro- ub. 30. If word of the pro- ub. 30. If word allows the pro- e installed and end of the pro- star ing e installed and end of the pro- star ing the pro- star ing the pro- star ing the pro- star ing e installed and end of the pro- star ing the pro- tar ing the pro- tar ing the pro- tar ing the pro- tar ing the pro- star ing the pro- tar ing
This well was shut in on 5/28/69 when product than 1 BOPD. Remedial acid work on 4/69 fail duction. We now propose to P & A well as fol 1. Spot 30 sx cement in 7" casing from 3310- 2. Cut off and recover 7" csg from about 100 3. Set cement plugs; 30 sx in & out of 7" st of 8-5/8" shoe @ 885' & 10 sx in top of w Salt gel mud will be used to spot all plugs. will remain intact. A dry hole marker will b cleared & levelled. RECEIVED JUN 4 1970 JUN 13. I hereby certify that the foregoing is grue and correct SIGNED Automotion (This space for Federal or State office use)	ion dropped to less ed to increase pro- lows: Una routing of the pro- lows: Una routing of the pro- lows: Una routing of the pro- ub. 30. If word of the pro- ub. 30. If word allows the pro- e installed and end of the pro- star ing e installed and end of the pro- star ing the pro- star ing the pro- star ing the pro- star ing e installed and end of the pro- star ing the pro- tar ing the pro- tar ing the pro- tar ing the pro- tar ing the pro- star ing the pro- tar ing
This well was shut in on 5/28/69 when product than 1 BOPD. Remedial acid work on 4/69 fail duction. We now propose to P & A well as fol 1. Spot 30 sx cement in 7" casing from 3310- 2. Cut off and recover 7" csg from about 100 3. Set cement plugs; 30 sx in & out of 7" st of 8-5/8" shoe @ 885' & 10 sx in top of w Salt gel mud will be used to spot all plugs. will remain intact. A dry hole marker will b cleared & levelled. RECEIVED JUN 4 1970 JUN B. C. C. ARTESIA, DFFICE BIONED MATCHESSION TITLE (This space for Federal or State office use)	ion dropped to less ion dropped to less ed to increase pro- lows: Unated and the string also be able to work of a string of 1200 and the string string ell. also be able to an another a bout string e installed and string to some the string of the string of the string of the string e installed and the string of the string of the string of the string of the string of the string of the string of the string of string of the string of the string of the string of string of the string of the string of the string of string of the string of the string of the string of string of the string of the string of the string of string of the string of the string of the string of string of the string of the string of the string of string of the string of the string of the string of the string of string of the string of the string of the string of the string of string of the string of the str

r