

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEYSUBMIT IN THE  
(Other Instru  
verse side)

ICATE\*

Form approved.  
Budget Bureau No. 42-R1424

5. LEASE DESIGNATION AND SERIAL NO.

LC 047633 (b)

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

L.M. Swearingen "B"

9. WELL NO.

5

10. FIELD AND POOL, OR WILDCAT

Shugart-Cases

11. SEC., T., R., M., OR BLK. AND  
SURVEY OR AREA

Sec. 14-18S-31E

12. COUNTY OR PARISH

Eddy

13. STATE

N.M.

1. OIL ☒ GAS ☐  
WELL WELL OTHER

2. NAME OF OPERATOR

Atlantic Richfield Company

3. ADDRESS OF OPERATOR

P.O. Box 1978, Roswell, New Mexico 88101

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.  
See also space 17 below.)  
At surface

660' FSL &amp; 1980' FEL Unit Letter O

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3710' CTF

## 16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON\*

CHANGE PLANS

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

SUBSEQUENT REPORT OF:

REPAIRING WELL

ALTERING CASING

ABANDONMENT\*

(NOTE: Report results of multiple completion on Well  
Completion or Recompletion Report and Log form.)17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any  
proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones perti-  
nent to this work.) \*

This well has been plugged &amp; abandoned in the following manner:

Spotted 30 sk Class A cement plug 3480-3250'. Cement plug did not hold. Set 5½" CIBP @ 3035'. Shot 5½" casing free @ 1272'. Pulled 39 jts 5½" 14# Cl. II casing = 1272'. Spotted 30 sk Class A cement plug half in & half out of 5½" casing stub @ 1272'. Spotted 30 sk Class A cement plug half in & half out of 8-5/8" casing shoe @ 889'. Spotted 10 sk Class A cement plug in surface. Erected dry hole marker. 9#/gal gel mud was used to spot all plugs. 8-5/8" casing remains intact. Well plugged & abandoned 11/7/70.

Change in plans verbally approved by Mr. Jim Knauf

Your office will be notified by letter when location is ready for inspection.

18. I hereby certify that the foregoing is true and correct

SIGNED

D.D. Ditcher

TITLE

Dist. Drlg. Supervisor

DATE

11-11-70

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

APPROVED  
NOV 15 1971  
R. L. BECKMAN  
ACTING DISTRICT ENGINEER

\*See Instructions on Reverse Side