

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

N.M. Oil Cons. Division
811 S. 1st Street
Artesia, NM 88210-2834

SEP 23 1996

FORM APPROVED
Budget Bureau No. 1004-0115
Expires: September 20, 1990

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

Mack Energy Corporation

3. Address and Telephone No.

P. O. Box 960, Artesia, NM 88211 (505)748-1288

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

Sec.18, T-1-S R-31-E 2310' ENL & 330' FWL

5. Lease Designation and Serial No.

LC-029393-D

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

Shugart 18 Queen Unit

8. Well Name and No.

#5
Shugart 18 Queen Unit

9. API Well No.

30-115-05580

10. Field and Pool, or Exploratory Area

Shugart (YSRQ6)

11. County or Parish, State

Eddy, NM

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent
☒ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

- ☒ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☐ Other

- ☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

- 1) Set CIBP @ 2950' cap W/35 sx cement
- 2) Load hole with mud
- 3) Perforate 4 1/2 casing @ 1710' unable to pump into perforations Spot 25 sx cement plug across perforations @ 1763' W.O.C. Approval to spot cement plug by Gene W/BLM in Carlsbad, NM Tag cement top @ 1453'
- 4) Perforate 4 1/2 casing @ 775' Squeeze W/75 sacks cement W.O.C. Tag cement top @ 548'
- 5) Perforate 4 1/2 casing @ 60' circulate cement to surface between 4 1/2 & 8-5/8 leaving 4 1/2 full Set PA marker
- 6) Job completed 9-12-96

Post ID-2
10-25-96
PKA

Approved on behalf of the well owner.
Liability under bond is retained until
surface restoration is completed.

14. I hereby certify that the foregoing is true and correct

Signed *David R. Glass*

Title *Superintendent*

Date 9-18-96

(This space for Federal or State office use)

(ORIG. SGD.) DAVID R. GLASS

Approved by
Conditions of approval, if any:

Title PETROLEUM ENGINEER

Date OCT 01 1996