


(SUBMIT IN TRIPLICATE)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

Land Office Las Cruces  
Lease No. 029392 b  
Unit Lease



SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL.....	<input checked="" type="checkbox"/>	SUBSEQUENT REPORT OF WATER SHUT-OFF.....	
NOTICE OF INTENTION TO CHANGE PLANS.....		SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.....	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....		SUBSEQUENT REPORT OF ALTERING CASING.....	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.....		SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR.....	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....		SUBSEQUENT REPORT OF ABANDONMENT.....	
NOTICE OF INTENTION TO PULL OR ALTER CASING.....		SUPPLEMENTARY WELL HISTORY.....	
NOTICE OF INTENTION TO ABANDON WELL.....			

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

Greenwood Unit No. 6

September 14, 1959

Well No. 6 is located 1880 ft. from XX line and 1980 ft. from E line of sec. 26

NW/4 SE/4 Section 26 18S 31E N. M. P. M.  
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)

Shugart Shinarump Pennsylvanian Eddy New Mexico  
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is \_\_\_\_\_ ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

It is our intention to drill a well with rotary tools at the above location to a total depth of approximately 11,900'. All casing points will be cemented in accordance with approved methods of the U. S. Geological Survey and any other special requirements will be complied with.

It is planned to use the following casing pattern: 17 1/2" hole to be drilled, 13 3/8" casing to be set at approximately 800' and cemented with 500 sacks, cement to be circulated. 12 1/4" hole to be drilled, 8 5/8" casing to be set at approximately 6,400' and cemented with 2550 sacks, cement to be circulated. 7 5/8" hole to be drilled, 5 1/2" casing to be set at approximately 11,900' and cemented with 650 sacks. It is calculated the cement for the 5 1/2" casing will return to 7500'.

Approval to produce this well upon completion is also requested.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Continental Oil Company

Address Rowley Bldg.

Artesia, N. M.

By [Signature]

Title District Superintendent

OIL CONSERVATION COMMISSION		
ARTESIA DISTRICT OFFICE		
No. Copies Received		
	DATE RECEIVED	FILED
OPERATOR		
SANTA FE		
PRODUCTION OFFICE		
STATE LAND OFFICE		
U. S. O. S.		
TRANSPORTER		
FILE		
BUREAU OF MINES		