



Amoco Production Company

ENGINEERING CHART

SHEET NO.

OF

FILE

APPN

SUBJECT GREENWOOD Unit #1DATE 05-23-83BY BAWShugart - Silver DEVONIAN GAS660 FSL & 660 FSL, SEC 27, T 185, R 31 E
Eddy County, New Mexico

Completed: 2-20-57

Elev: 3659' R.D.B.
3641' G.L.

16" CSA 358'

42.8" ST ARMCO

Cmt w/ 790 SXS

Circ. 22" Hole

TCMT - 2000'

10 3/4" CSA 4677'

40.5" J-55 ST & C

45.5" S-80 ST & C

Cmt w/ 1600 SXS

TCMT - 2000' 13 3/4" Hole

TCMT - Apr 4640'
BTM CMT - Apr 6400'2 7/8" N-80 6.5#, 8" T₆
7 x 2 7/8" XL on off tool w/ 1.875 Profile

7 5/8" 29.7" 39" x 2 7/8" (Un. PKR VI)

CSA 11645

2 7/8" Box x 2 7/8" Pin Changeover

2 7/8" N-80 T₆ w/ F Nipple w/ 1.875 Profile2 7/8" T₆ landed at 12357'

TCMT - 7805'

ATOKA Perfs

10792 - 10832

7 5/8" CSA 11,915'

26.4" - 33.7" N-80 S-95

LTC AND ST & C 9 5/8" Hole

Cmt w/ 1000 SXS

TCMT - 7805'

Squeezed Perfs:

12,580-630, 12,655-700, 12,741-766,
12,835-863, 12,942-964

Dev.

Perfs: 12,470-12,500 w/ 2 JSPE

Perfs: 12,390-446 & 12,470-518 w/ 1 JSPE

Retainer 37" CL 12,543'. 6' Cmt. Cap

Fish in hole: 11' of 2" perforated
Sub.

Notes Dr. Pipe. Let in hole.

Top of fish - 13,010'

5" Liner 11,343'-13,001'

18" N-80 LTC

Cmt w/ 55 SXS Circ

6 3/8" Hole

TD - 13,446'

PBD - 12,542'