

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

NM OIL CONS COMMISSION
Drawer DD
Artesia, NM 88210

HOBBBS NEW MEXICO 88240
FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well
☐ Oil Well ☐ Gas Well ☒ Other Injection

2. Name of Operator

Xeric Oil & Gas Company

3. Address and Telephone No.

P.O. Box 51311, Midland, Texas 79710 (915) 683-3171

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

1980' FNL x 660' FWL, Unit E, Section 28, T-18-S, R-31-E

5. Lease Designation and Serial No.

LC-029390-A

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Keohane B Federal #1

9. API Well No.

30-015-05623

10. Field and Pool, or Exploratory Area

Shugart (Y-SR-Q-GB)

11. County or Parish, State

Eddy County, N. M.

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☒ Notice of Intent
☐ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

- ☒ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☐ Other
☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

PROCEDURE:

1. Set 4 1/2" CIBP @ 3500' and cap with 35' of cement,
2. Cut and pull 4 1/2" casing as deep as possible,
3. Spot 35 sxs of cement in and out of stub and tag,
4. Spot 50 sxs of cement @ 298'-198' and tag,
5. Spot 10 sxs of cement @ surface,
6. Install dry hole marker.

RECEIVED

MAR 23 10 23 AM '94

CRUDE OIL

Perfs ←
At 3265 - CK casing for hole
after CIBP set



14. I hereby certify that the foregoing is true and correct

Signed Joe G. Lara Title Supervisor

Date 3-10-94

(This space for Federal or State office use)

Approved by (ORIG. SGD.) JOE G. LARA

Title PETROLEUM ENGINEER

Date 4/5/94

Conditions of approval, if any:

see attached