

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN T LICATE*
(Other instru on re-
verse side)Form approved.
Budget Bureau No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐		7. UNIT AGREEMENT NAME East Shugart Unit w/
2. NAME OF OPERATOR Atlantic Richfield Company		8. FARM OR LEASE NAME East Shugart Unit
3. ADDRESS OF OPERATOR P. O. Box 1978, Roswell, New Mexico		9. WELL NO. 14
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) At surface 2310' PNL & 1650' FEL (Unit G)		10. CLASSIFIED AND POOL, OR WILDCAT Shugart-Queen
14. PERMIT NO.		11. SEC., T., R., M., OR BLM. AND SURVEY OR AREA Sec. 34, T-18-31E
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 3634' DF		12. COUNTY OR PARISH Ady
		13. STATE N.M.

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF	☐	PULL OR ALTER CASING	☐
FRACTURE TREAT	☒	MULTIPLE COMPLETE	☐
SHOOT OR ACIDIZE	☒	ABANDON*	☐
REPAIR WELL	☐	CHANGE PLANS	☐
(Other)	Add Yates perfs		☒

SUBSEQUENT REPORT OF:

WATER SHUT-OFF	☐	REPAIRING WELL	☐
FRACTURE TREATMENT	☐	ALTERING CASING	☐
SHOOTING OR ACIDIZING	☐	ABANDONMENT*	☐
(Other)			

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

In order to prepare this producing well for expected waterflood response, we propose to perform the following work.

1. Run cement bond log. Locate top of cement. Shoot 4 holes at cement top and cement behind 4-1/2" csg w/200 sx cement. Clear holes w/2 bbls water. WOC 8 hrs and squeeze cement w/50 sx.
2. Add Queen perforations 3331-33, 3336-41, 3414-21, 3427-32, 3635-54 w/2 JSPP and treat w/40,000# 20/40 sd in 40,000 gal slick water.
3. Add Yates perfs, 1 hole each, @ 2633, 2638, 2655, 2694, 2701, 2705, 2746, 2753, 2757, 2764, 2769 (if necessary to squeeze off old perfs) and treat w/30,000# 20/40 sd in 30,000 gal slick water.

Work to commence about July 7, 1969.

RECEIVED

JUL 7 1969

18. I hereby certify that foregoing is true and correct

SIGNED **O. D. Bretches**TITLE **Dist. Dirg. Supervisor**

(This space for Federal or State office use)

APPROVED BY **PROPOSES ONLY**
CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

ACCEPTED FOR RECORD
JUL - 8 1969
Date

ACTING

District Engineer

APPROVED

JUL - 8 1969

H. E. BEEKMAN
ACTING DISTRICT ENGINEER

*See Instructions on Reverse Side

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site condition or final inspection looking to approval of the abandonment.

U.S. GOVERNMENT PRINTING OFFICE: 1963-O-468229

507-851

APPROVED

JUL - 1 1963
A. C. REEKMAN

RECEIVED
JUL - 2 1963
JUL - 2 1963
JUL - 2 1963