

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIP DATE*
(Other Instructions on reverse side)

Form approved.
Budget Bureau No. 1004-0135
Expires August 31, 1985

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

RECEIVED

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER WIW		7. UNIT AGREEMENT NAME 8910115720
2. NAME OF OPERATOR Hondo Oil & Gas Company ✓		8. FARM OR LEASE NAME East Shugart Unit
3. ADDRESS OF OPERATOR P. O. Box 2208, Roswell, NM 88202		9. WELL NO. 3
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) At surface 990' FNL & 330' FEL		10. FIELD AND POOL, OR WILDCAT Shugart Yates 7R-Qn-Grbg
14. PERMIT NO.		15. ELEVATIONS (Show whether DF, RT, GR, etc.)
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 34-T18S-R31E		12. COUNTY OR PARISH Eddy
		13. STATE NM

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREATMENT

ALTERING CASING

SHOOTING OR ACIDIZING

ABANDONMENT*

(Other) Clean out csg & reperf.

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

POH w/ tbg. milled over packer, POH w/ packer. Perforated 3324', 3326', 3330', 3403', 3410', 3419', 3430', 3434', 3440', 3543', 3544', 3545', 3546', 3651', 3655', 3658', 3660', 3687', 3691', 3692', 3699', 3700', 3705', 3706', 3708', 3718', 3721', 3722', 3765', 3775', 3776', 3777', 3778', 3819', 3827', 3828', 3829', 3838', 3839', 3840', 3841', 3842', 3843', 3844',

Acidized 3819'-3844' w/ 500 gals SWIC and 1000 gals 15% NeFe, ISIP 1000 psi.

Acidized 3765'-3778' w/ 500 gals SWIC + 1000 gals 15% NeFe, ISIP 850 psi.

Acidized 3543'-3722' w/ 1000 gals SWIC & 2000 gals 15% NeFe, ISIP 850 psi.

Acidized 3324'-3440' w/1000 gals SWIC & 2000 gals 15% NeFe, ISIP 1060 psi.

Ran 99 jts 2 3/8" J-55 8rd tbg w/ ceramic coating - 3202.69' 7" packer @ 3208', tested @ 340 psi - 20 min held O.K.

18. I hereby certify that the foregoing is true and correct

SIGNED Ron Brown

TITLE Petroleum Engineer

DATE 01/08/90

(This space for Federal or State office use)

APPROVED BY _____

TITLE _____

DATE _____

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side