Form 3160-5 (November 1983) (Formerly 9-331)	UNIT STATES DEPARTMENT JF THE INTERI BUREAU OF LAND MANAGEMENT		5. LEASE DESIGNATION AN	. 1985 C
(Do not use th	NDRY NOTICES AND REPORTS C s form for proposals to drill or to deepen or plug bi Use "APPLICATION FOR PERMIT" for such pr	DN WELLS ack to a different reservoir. oposals.)	0. IF INDIAN, ALLOTTEE O	
		JUL 24 IT 45 AM	JUNIT AGREEMENT NAME	
2. NAME OF OPERATOR	L_J OTHER	CARL	East Shugart Un	<u>it</u>
	(0.0. (omponie)	AREA Contraction of the	S	
Hondo Oil & Gas Company 3. ADDRESS OF OPERATOR			9. WELL NO.	
P. O. Box 2208, Roswell, NM 88202			2	
4. LOCATION OF WELL	Report location clearly and in accordance with any !	State requirements.*	10. FIELD AND POOL, OR W	ILDCAT
See also space 17 below.) At surface			Shugart Yates 7R-On-Grbg	
990' FNL & 1650' FEL			11. SEC., T., B., M., OR BLE. AND	
			SURVEY OR ARMA	
• ¹⁸			Sec. 34-T18S-R	31E
14. PERMIT NO. 15. ELEVATIONS (Show whether DF, RT, CR,		RT, GR, etc.)	12. COUNTY OR PARISH 1	3. STATE
	· .	·	Eddy	NM
16.	Check Appropriate Box To Indicate N	ature of Natice Report or C	Other Data	
	NOTICE OF INTENTION TO :			
			UENT REPORT OF:	
TEST WATER SHUT-	.	WATER SHUT-OFF	REPAIRING WEL	L
FRACTURE TREAT	MULTIPLE COMPLETE	FRACTUBE TREATMENT X	ALTERING CASIN	10
SHOOT OR ACIDIZE	ABANDON*	SHOOTING OR ACIDIZING X	ABANDONMENT*	
REPAIR WELL (Other)	CHANGE PLANS	(Other)	of multiple completion on	Well
nent to this work. 6/06/90	Swaged well out to 3921' TD.	ons and measured and true vertic	al depths for all markers an	1d zones perti-
6/08/90	Perforated 3300-3882' with 64 gal. 15% diesel emulsified aci			
6/09-11/90				
6/12/90	Frac'd 3739-3882' with 30,000 sand. Flowed back.	gal. gelled water + 6	50,000# 12/20	
6/13-14/90	Swabbed and flowed well back.			
6/15/90	Acidized 3584-3706' with 3000 Flowed well back.	gal. 15% DEA acid + 4	40 ball sealers.	
6/16-19/90	Swabbed and flowed well back.			RECEIVED
6/20/90				
6/21-28/90	2000# rock salt. Flowed and s	wapped well back.	•	
6/21-28/90	Swabbed and flowed well back.	ani 150 mmm		JUL 27 '90
0/29/90	Acidized 3379-3428' with 3000 sealers. Swabbed well back.	yar. 10% NEFE acid us	sing 45 ball	JUL CI JU
7/03/90	Swabbed well back. Acidized 3. acid.	300-3306' with 2000 g	gal. 15% NEFE	O. C. D.
7/05/90	Flowed well back.			ARTISTA,
7/06/90	Ran in hole with 2" x l 1/2" x tubing with the SN set @ 3883'	20' RWBC pump and 12	23 jts. 2 3/8"	
7/07/90		- 		
18. I hereby certify tha	the foregoing is true and correct			
SIGNED	L. Johanon TITLE Eng.	ineering Technician	DATE7/19/90	0
(This space for Fed	ral or State office use)			
APPROVED BY		Af	DATE	
	PPROVAL, IF ANY:		UALN	

*See Instructions on Reverse Side

`