Form 3160-5 (June 1990)

any matter within its jurisdiction.

UT ED STATES DEPARTML. T OF THE INTERIOR **BUREAU OF LAND MANAGEMENT**

FORM APPROVED
Budget Bureau No. 1004-0135
Expires March 31, 1993

CHAIDDY MOTICE	S AND REPORTS ON WELLS	5. Lease Designation and Serial No.
SUNDAT NOTICE	or to deepen or reentry to a different reservoir.	NM10190
Do not use this form for proposals to drill or to deepen or reentry to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals		6. If Indian, Allottee or Tribe Name
SURMI	T IN TRIPLICATE	N/A
3001111	THE THE EIGHT	7. If Unit or CA, Agreement Designation
1. Type of Well Oil Gas Well Other WIW		14-08-001-11572 East Shugart Ut
Name of Operator		
DÉVON ENERGY CORPORATION (NEVADA)		EAST SHUGART UNIT #6
Address and Telephone No.		9. API Well No.
20 NORTH BROADWAY, SUITE 1500, OKLAHOMA CITY, OKLAHOMA 73102 (405) 235-3611		30-015-05696
4. Location of Well (Footage. Sec., T., R., M., or Survey Description) 990' FNL & 2310' FWL, Unit C, Section 35-18S-31E		10. Field and Pool, or Exploratory Area
		Shugart (Y-7R-Q-GB)
350 1142 & 2010 1112, 0		11. County or Parish, State
		Eddy Cnty, NM
CHECK APPROPRIATE BOX	(s) TO INDICATE NATURE OF NOTICE, RE	
TYPE OF SUBMISSION	TYPE OF ACTIO	N 70 \$ 22
Notice of Intent	Abandonment	Change of Plans
	Recompletion	New Construction
Subsequent Report	Plugging Back	Non-Routine Fracturing
_	Casing Repair	Water Shut-Off
Final Abandonment Notice	Altering Casing	Conversion to Injection Dispose Water
	Other Replace the and acidize	(Note: Report results of multiple completion on Well
locations and measured and true vertical depths for all mark 01-03-96 thru 01-04-96 NU BOP	P. POH w/2 7/8" tbg and seal assembly. Ran	I.P.C. Baker anchor seal
01-03-96 thru 01-04-96 NU BOP assembly w/on-off tool, "F" profilmodel "D" packer at 2850'. Release Ran MIT test at 500 psi for 30 min Dowell acidized perfs 3360-3877' BPM w/1300 psi. ISIP 530 psi, 1 Replaced injection line. Returned	P. POH w/2 7/8" tbg and seal assembly. Ran e nipple and 87 jts 2 3/8" 4.7# J-55 8rd EUE ased on-off tool. Circ'd hole w/packer fluid. ns, held OK. w/5000 gals 15% NeFe acid + 500 gals Xyle 5 mins 250 psi. d to injection on 03-01-96.	I.P.C. Baker anchor seal I.P.C. tbg (TK-70). Stung into Latched onto on-off tool. CENTED and AIR 5 PR 1 5 1996
01-03-96 thru 01-04-96 NU BOP assembly w/on-off tool, "F" profilmodel "D" packer at 2850'. Release Ran MIT test at 500 psi for 30 min Dowell acidized perfs 3360-3877' BPM w/1300 psi. ISIP 530 psi, 1 Replaced injection line. Returned 03-04-96 Injected 394 BWPD w/	P. POH w/2 7/8" tbg and seal assembly. Ran e nipple and 87 jts 2 3/8" 4.7# J-55 8rd EUE ased on-off tool. Circ'd hole w/packer fluid. ns, held OK. w/5000 gals 15% NeFe acid + 500 gals Xyle 5 mins 250 psi. d to injection on 03-01-96. /180 psi injection press.	I.P.C. Baker anchor seal I.P.C. tbg (TK-70). Stung into Latched onto on-off tool. CEIVED and AIR 5
01-03-96 thru 01-04-96 NU BOP assembly w/on-off tool, "F" profilmodel "D" packer at 2850'. Release Ran MIT test at 500 psi for 30 min Dowell acidized perfs 3360-3877' BPM w/1300 psi. ISIP 530 psi, 1 Replaced injection line. Returned 03-04-96 Injected 394 BWPD w/	P. POH w/2 7/8" tbg and seal assembly. Ran e nipple and 87 jts 2 3/8" 4.7# J-55 8rd EUE ased on-off tool. Circ'd hole w/packer fluid. ns, held OK. w/5000 gals 15% NeFe acid + 500 gals Xyle 5 mins 250 psi. d to injection on 03-01-96. /180 psi injection press.	I.P.C. Baker anchor seal I.P.C. tbg (TK-70). Stung into Latched onto on-off tool. CEIVED The property of the
01-03-96 thru 01-04-96 NU BOP assembly w/on-off tool, "F" profilmodel "D" packer at 2850'. Release Ran MIT test at 500 psi for 30 min Dowell acidized perfs 3360-3877' BPM w/1300 psi. ISIP 530 psi, 1 Replaced injection line. Returned 03-04-96 Injected 394 BWPD w/	P. POH w/2 7/8" tbg and seal assembly. Ran e nipple and 87 jts 2 3/8" 4.7# J-55 8rd EUE ased on-off tool. Circ'd hole w/packer fluid. ns, held OK. w/5000 gals 15% NeFe acid + 500 gals Xyle 5 mins 250 psi. d to injection on 03-01-96. /180 psi injection press.	I.P.C. Baker anchor seal I.P.C. tbg (TK-70). Stung into Latched onto on-off tool. CEIVED The property of the
01-03-96 thru 01-04-96 NU BOP assembly w/on-off tool, "F" profilmodel "D" packer at 2850'. Release Ran MIT test at 500 psi for 30 min Dowell acidized perfs 3360-3877' BPM w/1300 psi. ISIP 530 psi, 1 Replaced injection line. Returned 03-04-96 Injected 394 BWPD w/	POH w/2 7/8" tbg and seal assembly. Ran e nipple and 87 jts 2 3/8" 4.7# J-55 8rd EUE assed on-off tool. Circ'd hole w/packer fluid. ns, held OK. w/5000 gals 15% NeFe acid + 500 gals Xyle 5 mins 250 psi. d to injection on 03-01-96. /180 psi injection press.	I.P.C. Baker anchor seal I.P.C. tbg (TK-70). Stung into Latched onto on-off tool. CEIVED at AIR 5 PR 1 5 1996 COIN. DIV.
01-03-96 thru 01-04-96 NU BOP assembly w/on-off tool, "F" profilmodel "D" packer at 2850'. Release Ran MIT test at 500 psi for 30 min Dowell acidized perfs 3360-3877' BPM w/1300 psi. ISIP 530 psi, 1 Replaced injection line. Returned 03-04-96 Injected 394 BWPD w/ 14. Thereby certify that the foregoing is true and correct Signed Candace R. Lack (This space for Federal or State office use)	POH w/2 7/8" tbg and seal assembly. Ran e nipple and 87 jts 2 3/8" 4.7# J-55 8rd EUE ased on-off tool. Circ'd hole w/packer fluid. ns, held OK. w/5000 gals 15% NeFe acid + 500 gals Xyle 5 mins 250 psi. d to injection on 03-01-96. /180 psi injection press. Candace R. Graham Title Engineering Technician	I.P.C. Baker anchor seal I.P.C. tbg (TK-70). Stung into Latched onto on-off tool. CEIVED at AIR 5 PR 1 5 1996 COIN. DIV. DIST. 2
01-03-96 thru 01-04-96 NU BOP assembly w/on-off tool, "F" profilmodel "D" packer at 2850'. Release Ran MIT test at 500 psi for 30 min Dowell acidized perfs 3360-3877' BPM w/1300 psi. ISIP 530 psi, 1 Replaced injection line. Returned 03-04-96 Injected 394 BWPD w/	POH w/2 7/8" tbg and seal assembly. Ran e nipple and 87 jts 2 3/8" 4.7# J-55 8rd EUE assed on-off tool. Circ'd hole w/packer fluid. ns, held OK. w/5000 gals 15% NeFe acid + 500 gals Xyle 5 mins 250 psi. d to injection on 03-01-96. /180 psi injection press.	I.P.C. Baker anchor seal I.P.C. tbg (TK-70). Stung into Latched onto on-off tool. CEIVED at AIR 5 PR 1 5 1996 COIN. DIV.
01-03-96 thru 01-04-96 NU BOP assembly w/on-off tool, "F" profilmodel "D" packer at 2850'. Release Ran MIT test at 500 psi for 30 min Dowell acidized perfs 3360-3877' BPM w/1300 psi. ISIP 530 psi, 1 Replaced injection line. Returned	POH w/2 7/8" tbg and seal assembly. Ran e nipple and 87 jts 2 3/8" 4.7# J-55 8rd EUE ased on-off tool. Circ'd hole w/packer fluid. ns, held OK. w/5000 gals 15% NeFe acid + 500 gals Xyle 5 mins 250 psi. d to injection on 03-01-96. /180 psi injection press. Candace R. Graham Title Engineering Technician	I.P.C. Baker anchor seal I.P.C. tbg (TK-70). Stung into Latched onto on-off tool. CEIVED at AIR 5 PR 1 5 1996 COIN. DIV.

