


N

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

AREA 640 ACRES
LOCATE WELL CORRECTLY

WELL RECORD



Mail to Oil Conservation Commission, Santa Fe, New Mexico, or its proper agent not more than twenty days after completion of well. Follow instructions in the Rules and Regulations of the Commission. Indicate questionable data by following it with (?). SUBMIT IN TRIPPLICATE. FORM C-110 WILL NOT BE APPROVED UNTIL FORM C-105 IS PROPERLY FILLED OUT.

J. F. Postelle P. O. Box 2326, Odessa, Texas
Company or Operator Address

Ohio- State Well No. 1 1/4 of Sec. 2 T. 19S
R. 31E N. M. P. M. Shugart Field, Eddy County.
Well is 330 feet south of the North line and 1650 feet west of the East line of Sec. 2
If State land the oil and gas lease is No. B-2294 Assignment No. 3
If patented land the owner is _____ Address _____
If Government land the permittee is _____ Address _____
The Lessee is The Ohio Oil Company Address Oil & Gas Bldg., Houston 2, Texas
Drilling commenced October 9 19 45 Drilling was completed December 7 19 45
Name of drilling contractor Postelle and Flack Address P. O. Box 2326, Odessa, Texas
Elevation above sea level at top of casing 3626 feet.
The information given is to be kept confidential until No requirements 19 _____

OIL SANDS OR ZONES

No. 1, from 2873 to 2875 Show _____ No. 4, from 3893 to 3913 Show Oil and Gas
No. 2, from 3220 to 3243 Show _____ No. 5, from _____ to _____
No. 3, from 3424 to 3439 Show _____ No. 6, from _____ to _____

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from 2875 to 2891 feet. 600 feet in hole
No. 2, from _____ to _____ feet. _____
No. 3, from _____ to _____ feet. _____
No. 4, from _____ to _____ feet. _____

CASING RECORD

SIZE	WEIGHT PER FOOT	THREADS PER INCH	MAKE	AMOUNT	KIND OF SHOE	CUT & FILLED FROM	PERFORATED		PURPOSE
							FROM	TO	
<u>8-5/8"</u>	<u>28#</u>	<u>8</u>	<u>SH</u>	<u>910'</u>	<u>TP</u>				
<u>7"</u>	<u>20#</u>	<u>8</u>	<u>Nat.</u>	<u>3337'</u>	<u>TP</u>				

MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
<u>10"</u>	<u>8-5/8"</u>	<u>910'</u>	<u>50</u>	<u>Halliburton</u>		
<u>8"</u>	<u>7"</u>	<u>3337'</u>		<u>"</u>	<u>Aquafol</u>	<u>15 sacks</u>

PLUGS AND ADAPTERS

Heaving plug—Material 3 wooden Length 3' Depth Set 9400', 2280', 900'
Adapters—Material None Size _____

RECORD OF SHOOTING OR CHEMICAL TREATMENT

SIZE	SHELL USED	EXPLOSIVE OR CHEMICAL USED	QUANTITY	DATE	DEPTH SHOT OR TREATED	DEPTH CLEANED OUT

Results of shooting or chemical treatment _____

RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto.

TOOLS USED

Rotary tools were used from _____ feet to _____ feet, and from _____ feet to _____ feet
Cable tools were used from 0 feet to 3953 feet, and from _____ feet to _____ feet

PRODUCTION

Put to producing None 19 _____
The production of the first 24 hours was _____ barrels of fluid of which _____ % was oil; _____ % emulsion; _____ % water; and _____ % sediment. Gravity, Be _____
If gas well, cu. ft. per 24 hours _____ Gallons gasoline per 1,000 cu. ft. of gas _____
Rock pressure, lbs. per sq. in. _____

EMPLOYEES

Frank Starkey Driller G. C. Pratt Driller
R. A. Phillips Driller _____ Driller

FORMATION RECORD ON OTHER SIDE

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

Subscribed and sworn to before me this 13thOdessa, Texas December 13, 1945day of December 1945Name J. F. PostellePosition OwnerRepresenting J. F. Postelle
Company or OperatorMy Commission expires June 1, 1947Address P. O. Box 2326, Odessa, Texas

FORMATION RECORD

FROM	TO	THICKNESS IN FEET	FORMATION
0	15	15	Calichi
15	110	95	Red Rock
110	120	10	Red Sand
120	305	185	Red Sand- Red Rock
305	320	15	Red Sand
320	425	105	Red Rock
425	470	45	Red Rock- Sandy
470	650	180	Red Rock
650	735	85	Red Rock- Sand
735	765	30	Red Rock
765	790	25	Anhydrite
790	805	15	Red Rock
805	880	75	Anhydrite-Lime-Shells
880	890	10	Anhydrite
890	903	13	Salt
903	960	57	Anhydrite
960	971	11	Red Rock
971	977	6	Anhydrite- Salt
977	986	9	Anhydrite- Red Rock
986	1340	354	Salt- Red Rock
1340	2100	760	Salt
2100	2120	20	Anhydrite
2120	2280	160	Salt
2280	2335	55	Anhydrite
2335	2385	50	Anhydrite- Red Rock
2385	2550	165	Anhydrite
2550	2673	123	Anhydrite- Red Rock
2673	2690	17	Anhydrite
2690	2720	30	Lime
2720	2746	26	Sandy Lime
2746	2775	29	Anhydrite- Lime- Red Rock
2775	2795	20	Sand
2795	2809	14	Lime
2809	2814	5	Sand
2814	2836	22	Lime
2836	2873	37	Grey Lime
2873	2891	18	Red Sand
2891	2905	14	2873-2875 - Show Oil
2905	2915	10	2875-2891 - "ater
2915	2920	5	Grey Lime
2920	2925	5	Red Sand
2925	2930	5	Red Sandy Shale
2930	3039	9	White Lime
3039	3177	138	Pink Lime
3177	3192	15	Lime-Grey
3192	3220	8	Lime
3220	3243	23	Red Lime
3243	3261	18	Lime
3261	3275	14	Sand (Show of Oil)
3275	3318	43	Lime
3318	3375	57	Lime- Sand
3375	3412	57	Lime
3412	3466	54	Grey Lime
3466	3473	7	Lime
3473	3511	38	Lime-Sand
3511	3672	61	3424- 3439- Show Oil
3672	3683	11	Red Sand
3683	3715	32	Grey Lime
3715	3723	8	Lime
3723	3807	84	Sand-Sharp
3807	3815	8	Lime
3815	3829	14	Grey Sand
3829	3857	28	Lime
3857	3875	18	Sand
3875	3881	6	Sandy Lime
3881	3893	12	Lime
3893	3913	20	Sandy Lime
3913	3930	17	Grey Sand
3930	3953	23	Sand- Lime
			Sand
			3905-3913- Show Oil and Gas
			Sandy Lime
			Lime Grey