

This is a corrected application to abandon well.

Form 9-331a
(Feb. 1951)

Budget Bureau No. 42-R358.4.
Approval expires 12-31-60.

(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office Artesia

Lease No. LC - 64577-E

Unit _____
RECEIVED

MAY 29 1961

SUNDRY NOTICES AND REPORTS ON WELLS

O. C. C.
ARTESIA, OFFICE

NOTICE OF INTENTION TO DRILL.....	SUBSEQUENT REPORT OF WATER SHUT-OFF.....
NOTICE OF INTENTION TO CHANGE PLANS.....	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.....
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....	SUBSEQUENT REPORT OF ALTERING CASING.....
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.....	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR.....
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....	SUBSEQUENT REPORT OF ABANDONMENT.....
NOTICE OF INTENTION TO PULL OR ALTER CASING.....	SUPPLEMENTARY WELL HISTORY.....
NOTICE OF INTENTION TO ABANDON WELL..... <u>X</u>	

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

Lease No. 192660

TEXACO Inc.

P.O. Box 352

B. I. Hanson Federal "B"

Midland, Texas

May 17, 1961

Well No. 1 is located 2313 ft. from N line and 991 ft. from E line of sec. 3

NW/4, SW/4, Sec. 3
($\frac{1}{4}$ Sec. and Sec. No.)

T-19-S
(Twp.)

R-31-E
(Range)

NMPM
(Meridian)

Shugart

(Field)

Eddy

(County or Subdivision)

New Mexico

(State or Territory)

The elevation of the derrick floor above sea level is 3609 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

We propose to plug and abandon subject well as follows:

1. Spot 75 sack plug from 3375' - 3675'.
2. Cut off $4\frac{1}{2}$ " csg at approx. 2600' and pull (top cmt. @ 2600')
3. Spot 25 sx plug from 50' below to 50' above top of now-recoverable $4\frac{1}{2}$ " csg.
4. Spot 25 sx plug 2200' to 2300'.
5. Spot 25 sx plug 865' to 965'.
6. Spot 25 sx cement plug from 650' to 750' (over surface casing seat).
7. Spot 15 sx plug in surface, install $4\frac{1}{2}$ " marker above ground level as per U.S.G.S. regulations. Clean location for inspection.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company TEXACO Inc.

Address P.O. Box 352

Midland, Texas

J. G. Blevins, Jr.

By [Signature]

Title Assistant District Superintendent