		· · · · ·	C. G. Lity			N' M	0560	チョ
rorm 9–331 (May 1963)	DEPAR	UNITED STATI	INTERIOR	Arbon was to	PLICATE.	For Bud	m al. loved. Iget susceau A SIGNATION AND 5709	No. 42
•		DTICES AND REF		WELLS to a different reserv	oir.	6. IF INDIAN	ALLOTTEE OF	TRIB
1. OIL <b>V</b> GAS						7. UNIT AGR	EMENT NAME	
WELL X WELL OTHER 2. NAME OF OPERATOR						8. FARM OR ALEASE NAME		
	t A. Hans	son		<u> </u>			Federa	1 🗰
3. ADDRESS OF OPER		5, Roswell, N	low Moric	0		9. WELL NO.		
4. LOCATION OF WEL	L (Report location	clearly and in accordance					D POOL, OR W	ILDCA
See also space 17 below.) At surface 330' FSL & 1800' FEL Sec. 6, T-19-5, R-31-E, N.M.P.M.						Shugart - Queen 11. BEC., T., B., M., OB BLK. AND		
		ly County, Ne				SURVE	T OR AREA	
14. PERMIT NO.	·	15. ELEVATIONS (Show		GR, etc.)			OR PARISH 1	
		353	37° DF			Eddy	N	• M
16.	Check A	Appropriate Box To i	indi <mark>cate Natur</mark>	e of Notice, Re	port, or O	ther Data		
	NOTICE OF INT	BNTION TO:			SUBSEQUI	INT REPORT O	<b>F</b> :	_
TEST WATER SH	UT-0 <b>FF</b>	PULL OR ALTER CASING		WATER SHUT-OFF			EPAIRING WEL	1-
FRACTURE TREAT Shoot or acidiz		MULTIPLE COMPLETE Abandon*	x	FRACTURE TREATM			LTERING CASI BANDONMENT <sup>®</sup>	1-
REPAIR WELL		CHANGE PLANS		(Other)				[
(Other)		PPERATIONS (Clearly state		Completion	or Recomple	tion Report a	nd Log form.)	)
nent to this wo T.D. @ 3 8-5/8" @	rk.)* 310* P.F	3.T.D. & 3298 50 sx. 5-1/	3' Perfs	and measured and	3263 <b>•</b>			
T.D. @ 3 8-5/8" @ It is pr	310' P.F 200' w/9	3.T.D. & 3298 50 sx. 5-1/ 5 plug and at	3' Perfs /2"@329	and measured and . @ 3212- 9' w/150	3263 <b>'</b> <b>s x .</b>			
T.D. @ 3 8-5/8" @ It is pr followin	310' P.F 200' w/ oposed to g manner:	B.T.D. & 3298 50 sx. 5-1/ p plug and at	3' Perfs /2"@ 329 Dandon th	and measured and . @ 3212- 9' w/150 he caption	3263 <b>'</b> <b>s x .</b>			
T.D. @ 3 8-5/8" @ It is pr followin 1.	310' P.F 200' w/9 oposed to g manner: Displace Spot a 2	3.T.D. & 3298 50 sx. 5-1/ p plug and at hole with h 20 sx. cmt. p	3' Perfs 2" @ 329 Dandon th Deavy mud Dlug @ 31	and measured and 9' w/150 1e caption 27-3298'	3263 sx. ed wel	l in th perfs.		
T.D. @ 3 8-5/8" @ It is pr followin 1. 2. 3.	310' P.F 200' w/9 oposed to g manner: Displace Spot a 2 Attempt	B.T.D. @ 3298 50 sx. 5-1/ p plug and at hole with H 20 sx. cmt. p to recover a	3' Perfs 2" @ 329 Dandon th Deavy mud plug @ 31 as much 5	and measured and (@ 3212-1) (9' w/150) (a caption) (27-3298') (5-1/2" cas)	3263 sx. ed wel across ing as	l in th perfs. possit	le ble.	
T.D. @ 3 8-5/8" @ It is pr followin 1. 2. 3. 4.	310' P.F 200' w/9 oposed to g manner: Displace Spot a 2 Attempt Spot a 2	B.T.D. @ 3298 50 sx. 5-1/ o plug and at hole with H 20 sx. cmt. p to recover a 20 sx. cmt. p	3' Perfs 2" @ 329 Dandon th Deavy mud plug @ 31 as much 5 Dlug in-a	and measured and . @ $3212 - 329$ . w/150 . caption . 27-3298 . 1/2" cast . and -out of	across 5-1/2	l in th perfs. possit " casir	bole. ng stub	
T.D. @ 3 8-5/8" @ It is pr followin 1. 2. 3. 4. 5. 6.	310' P.F 200' w/9 oposed to g manners Displace Spot a 2 Attempt Spot a 2 Spot a 2 Spot a 2	B.T.D. & 3298 50 sx. 5-1/ o plug and at hole with h 20 sx. cmt. p to recover a 20 sx. cmt. p 20 sx. cmt. p	9' Perfs 2" @ 329 Dandon th Deavy mud plug @ 31 as much 5 plug in-a plug @ 16 plug @ 0-	and measured and 9' w/150 1e caption 27-3298' -1/2" cas -1/2" cas -1/	across 5-1/2 -and-or	perfs. possit casir ut of 8	ole. ng stub 3-5/8".	
T.D. @ 3 8-5/8" @ It is pr followin 1. 2. 3. 4. 5.	310' P.F 200' w/9 oposed to g manner: Displace Spot a 2 Attempt Spot a 2 Spot a 2 Spot a 2 Spot a 2 Spot a 2 Spot a 2	B.T.D. & 3298 50 sx. 5-1/ o plug and at hole with h 20 sx. cmt. p to recover a 20 sx. cmt. p 20 sx. cmt. p	3' Perfs /2" @ 329 bandon th heavy mud plug @ 31 as much 5 plug in-a plug @ 16 plug @ 0- iry-hole	and measured and . @ $3212 - 329$ 	across 5-1/2 p of 8	l in th perfs. possit casir ut of & -5/8" c	ole. ng stub 3-5/8". casing.	
T.D. @ 3 8-5/8" @ It is pr followin 1. 2. 3. 4. 5. 6. 7.	310' P.F 200' w/9 oposed to g manner: Displace Spot a 2 Attempt Spot a 2 Spot a 2 Spot a 2 Spot a 2 Spot a 2 Spot a 2	B.T.D. @ 3298 50 sx. 5-1/ o plug and at hole with h 20 sx. cmt. p to recover a 20 sx. cmt. p 20 sx. cmt. p 10 sx. cmt. p regulation of	Perfs 2" @ 329 bandon th heavy mud plug @ 31 as much 5 plug in-a plug @ 16 plug @ 0- iry-hole or final	and measured and . @ $3212 - 329$ 	across 5-1/2 p of 8	l in th perfs. possit casir ut of & -5/8" c	ole. ng stub 3-5/8". casing.	
T.D. @ 3 8-5/8" @ It is pr followin 1. 2. 3. 4. 5. 6. 7.	310' P.F 200' w/9 oposed to g manner: Displace Spot a 2 Attempt Spot a 2 Spot a 2 Spot a 2 Spot a 2 Spot a 2 Spot a 2	B.T.D. @ 3298 50 sx. 5-1/ o plug and at hole with h 20 sx. cmt. p to recover a 20 sx. cmt. p 20 sx. cmt. p 10 sx. cmt. p regulation of	Perfs 2" @ 329 bandon th heavy mud plug @ 31 as much 5 plug in-a plug @ 16 plug @ 0- iry-hole or final	and measured and 9' w/150 caption 27-3298' 5-1/2" cast and-out of 7-214' in 33' in to marker. inspectio	across 5-1/2 p of 8	l in th perfs. possit casir ut of & -5/8" c	ole. ng stub 3-5/8". casing.	
T.D. @ 3 8-5/8" @ It is pr followin 1. 2. 3. 4. 5. 6. 7.	310' P.F 200' w/9 oposed to g manner: Displace Spot a 2 Attempt Spot a 2 Spot a 2 Spot a 2 Spot a 2 Spot a 2 Spot a 2	B.T.D. @ 3298 50 sx. 5-1/ o plug and at hole with h 20 sx. cmt. p to recover a 20 sx. cmt. p 20 sx. cmt. p 10 sx. cmt. p regulation of	Perfs 2" @ 329 bandon th heavy mud plug @ 31 as much 5 plug in-a plug @ 16 plug @ 0- iry-hole or final	and measured and 9' w/150 caption 27-3298' 5-1/2" cast and-out of 7-214' in 33' in to marker. inspectio	across ing as 5-1/2 and-or p of 8 n of U	1 in th perfs. possit " casir ut of & -5/8" o .S.G.S.	ole. ng stub 3-5/8". casing.	
T.D. @ 3 8-5/8" @ It is pr followin 1. 2. 3. 4. 5. 6. 7.	310' P.F 310' P.F 200' w/9 coposed to g manners Displace Spot a 2 Spot a 2 Spot a 2 Spot a 2 Spot a 2 Clean u	B.T.D. @ 3298 50 sx. 5-1/ o plug and at hole with h 20 sx. cmt. p to recover a 20 sx. cmt. p 20 sx. cmt. p 10 sx. cmt. p regulation of	Perfs 2" @ 329 bandon th heavy mud plug @ 31 as much 5 plug in-a plug @ 16 plug @ 0- iry-hole or final	and measured and 9' w/150 caption 27-3298' 5-1/2" cast and-out of 7-214' in 33' in to marker. inspectio	across ing as 5-1/2 and-or p of 8 n of U	1 in th perfs. possit casir ut of 8 -5/8" .S.G.S. .S.G.S.	ble. ag stub ag	
T.D. @ 3 8-5/8" @ It is pr followin 1. 2. 3. 4. 5. 6. 7. 8.	310' P.F 310' P.F 200' w/9 coposed to g manners Displace Spot a 2 Spot a 2 Spot a 2 Spot a 2 Spot a 2 Clean u	B.T.D. & 3298 50 sx. 5-1/ o plug and at the hole with f 20 sx. cmt. f to recover a 20 sx. cmt. f 20 sx. cmt. f 10 sx. cmt. f regulation for p location for	Perfs 2" @ 329 bandon th heavy mud plug @ 31 as much 5 plug @ 16 plug @ 0- iry-hole or final R E D E	and measured and 9' w/150 caption 27-3298' 5-1/2" cast and-out of 7-214' in 33' in to marker. inspectio	across ing as 5-1/2 -and-on p of 8 n of U	1 in th perfs. possit casir ut of 8 -5/8" .S.G.S. .S.G.S.	ble. ag stub ag	
T.D. @ 3 8-5/8" @ It is pr followin 1. 2. 3. 4. 5. 6. 7. 8.	310' P.F 310' P.F 200' w/9 coposed to g manners Displace Spot a 2 Spot a 2 Spot a 2 Spot a 2 Spot a 2 Clean u	B.T.D. @ 3298 50 sx. 5-1/ o plug and at the hole with H 20 sx. cmt. H to recover a 20 sx. cmt. H 20 sx. cmt. H 10 sx. cmt. H regulation for b location for	Perfs 2" @ 329 bandon th heavy mud plug @ 31 as much 5 plug @ 16 plug @ 0- iry-hole or final R E D E	and measured and . @ $3212 - 3298$ 	across ing as 5-1/2 -and-on p of 8 n of U	1 in th perfs. possit casir ut of 8 -5/8" .S.G.S. .S.G.S.	ole. ng stub 3-5/8". casing.	
T.D. @ 3 8-5/8" @ It is pr followin 1. 2. 3. 4. 5. 6. 7. 8. 8.	310' P.F 310' P.F 200' w/9 oposed to g manners Displace Spot a 2 Spot a 2 Spot a 2 Spot a 2 Spot a 2 Spot a 2 Spot a 2 Clean up	B.T.D. @ 3298 50 sx. 5-1/ o plug and at the hole with H 20 sx. cmt. H to recover a 20 sx. cmt. H 10 sx. cmt. H regulation for p location for g is true and correct	Perfs 2" @ 329 bandon th heavy mud plug @ 31 as much 5 plug @ 16 plug @ 0- iry-hole or final R E D E	and measured and . @ $3212 - 3298$ 	across ing as 5-1/2 -and-on p of 8 n of U	1 in th perfs. possit casir ut of 8 -5/8" .S.G.S. .S.G.S.	ble. ag stub ag	
T.D. @ 3 8-5/8" @ It is pr followin 1. 2. 3. 4. 5. 6. 7. 8. 8.	310' P.F 310' P.F 200' w/9 oposed to g manners Displace Spot a 2 Spot a 2 Spot a 2 Spot a 2 Spot a 2 Spot a 2 Spot a 2 Clean up	B.T.D. @ 3298 50 sx. 5-1/ o plug and at e hole with H 20 sx. cmt. H to recover a 20 sx. cmt. H 10 sx. cmt. H regulation for p location for	Perfs 2" @ 329 bandon th heavy mud plug @ 31 as much 5 plug @ 16 plug @ 16 plug @ 0- iry-hole or final REDE	and measured and . @ $3212 - 3298$ 	across ing as 5-1/2 -and-on p of 8 n of U	1 in th perfs. possit " casir ut of 8 -5/8" o .S.G.S. .S.G.S. .S.G.S. .S.G.S.	ble. ag stub ag	
T.D. @ 3 8-5/8" @ It is pr followin 1. 2. 3. 4. 5. 6. 7. 8. 8.	the the foregoln rederal or State	B.T.D. @ 3298 50 sx. 5-1/ o plug and at e hole with H 20 sx. cmt. H to recover a 20 sx. cmt. H 10 sx. cmt. H regulation for p location for	Perfs 2" @ 329 bandon th heavy mud plug @ 31 as much 5 plug @ 16 plug @ 16 plug @ 0- iry-hole or final REDE	and measured and . @ $3212 - 3298$ 	across ing as 5-1/2 -and-on p of 8 n of U	1 in th perfs. possit " casir ut of 8 -5/8" o .S.G.S. .S.G.S. .S.G.S. .S.G.S.	ble. ag stub ag	
T.D. @ 3 8-5/8" @ It is pr followin 1. 2. 3. 4. 5. 6. 7. 8. 8.	the the foregoln rederal or State	B.T.D. @ 3298 50 sx. 5-1/ o plug and at the hole with H 20 sx. cmt. H to recover a 20 sx. cmt. H 10 sx. cmt. H 10 sx. cmt. H regulation for plocation for g is true and correct	Perfs 2" @ 329 bandon th heavy mud plug @ 31 as much 5 plug @ 16 plug @ 16 plug @ 0- iry-hole or final REDE	and measured and (a) $3212-1$ (b) w/150 (c) a caption (c) $27-3298'$ (c) $-3298'$ (c) $-3298'$	across ing as 5-1/2 -and-on p of 8 n of U	1 in th perfs. possit " casir ut of 8 -5/8" o .S.G.S. .S.G.S. .S.G.S. .S.G.S.	ble. ag stub ag	