_	~	•		
	Budget Bureau No. 42-R358.4. Form Approved.			
Form 9-331 a (Feb. 1951)	Land Office Las Cruces			
	D STATES FOR 000 Lasso No016789			
DEPARTMENT OF THE INTERIOR				
GEOLOGICAL BURVEY PH 2 44				
	RECEI	VED		
SUNDRY NOTICES AN	D REPORTS ON WELLS JUL 2.6	196 <b>2</b>		
NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF	C		
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING			
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING			
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR			
NOTICE OF INTENTION TO SHOOT OR ACIDIZE				
NOTICE OF INTENTION TO PULL OR ALTER CASING				
NOTICE OF INTENTION TO ABANDON WELL	<u>}.</u>			
(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) U.S.A.Federal TEXACO Inc. P.O.Box 728				
	Hobbs, New Mexico July 23, 19.62			
Lease No. 163716 H	10005, New MCA100			
Well No is locatedft. from $\left\{ \begin{matrix} N \\ S \end{matrix} \right\}$ line andft. from $\left\{ \begin{matrix} E \\ W \end{matrix} \right\}$ line of sec				
$\frac{NE_{\frac{1}{4}}^{1}}{NW_{\frac{1}{4}}^{1}}, Sec. 6 \qquad 19-S \qquad 31-E \qquad NMPM$				
$\frac{\text{NE}\frac{1}{4}, \text{NW}\frac{1}{4}, \text{Sec. 6}}{(\frac{1}{4} \text{ Sec. and Sec. No.})} \qquad \frac{19-5}{(\text{Twp.})} \qquad (\text{Rat})$	nge) (Meridian)			
Shugart Edd (Field) (County or Su	ly New Mexico			
(Field) (County or Su	ubdivision) (State or Territory)			
The elevation of the derrick floor above sea level is 3530. ft.				
DETAILS OF WORK				
(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cement- ing points, and all other important proposed work)				
In abandoning subject well we propose to do the following:				
1 Mud un hole.				
2. Spot 70 sx cement plug from 3090' (top of Model "D" Packer) to				
2520' (top of Yates).				
	able 5 1/2" casing (top of cement at			
2065'). 4. Spot 35 sx cement plug from	50' below to 50' above top of non-			
recoverable 5 1/2" casing ar	nd a 35' sx cement plug from 550' to	-		
recoverable 5 1/2" casing and a 35' sx cement plug from 550' to 650' over the surface casing shoe.				
5. Spot 15 sx cement plug at the surface inside the 8 5/8" casing				
and install marker.				
· · · · · · · · · · · · · · · · · · ·				
I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.				
Company TEXACO Inc.				

Address P. O. Box 728

Hobbs, New Mexico

di namena i

J. G. Blevins, Jr.

, ·

By /	1 Blu	in for
- 1		Jey-
Title	Assistant	District

Superintendent

GPO 914974

2