

Form approved.
(May 1963)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPPLICATE*
(Other instructions on re-
verse side)

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

LC 063727-A

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1.

OIL WELL ☒ GAS WELL ☐ OTHER ☐

MAR 2 1965

2. NAME OF OPERATOR

American Petroleum Corp.

3. ADDRESS OF OPERATOR

Box 68, Hobbs, N.M. 88240

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

1980' FNL X 660' FEL, SEC. 12 (UNIT H, SE 1/4 NE 1/4)

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3640' RDB

7. UNIT AGREEMENT NAME

GREENWOOD UNIT

8. FARM OR LEASE NAME

9. WELL NO.

7

10. FIELD AND POOL, OR WILDCAT

GREENWOOD BONE SPRINGS

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

12-19-31 N.M.P.M.

12. COUNTY OR PARISH

13. STATE

Eddy

N.M.

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETION

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Bone Springs production has declined below economic limit. Workover possibilities exhausted. Plugging and abandonment proposed as follows:

"Spot cement plugs - 1005' across Strawn perms. 11092'-160', 150' plug on top of packer at 10,147' to isolate Wolfcamp perms. 10226-10212'; 150' plug, 8725'-8575' to cover Bone Springs' perms. 8668-8616.

Cut and pull 7" casing from approx. 6000' and spot 100' plug in and out of stub.

100' plug cut and in of shoe; 9 5/8" @ 4863, (9 5/8" stub @ 1753)

13 3/8" @ 875. 10' at surface and treat P+G marker

All intervals to be filled w/ mud laden filler

Restore ground to contour and make cleanup

(In accordance w/ telecon - Mark to Knapp - 2-23-65)

18. I hereby certify that the foregoing is true and correct

SIGNED

J. W. Smith

TITLE

Carea Engineer

DATE

2-25-65

(This space for Federal or State office use)

APPROVED BY

Mudolph C. Baird

TITLE

ACTING DISTRICT ENGINEER

DATE

FEB 25 1965

DIST. (0+11)

CONDITIONS OF APPROVAL, IF ANY:

0+4 - USGS
1 - Conoco
1 - Carper
1 - Shell
1 - State land

1 - JWB
1 - SusP
1 - WIS

*See Instructions on Reverse Side

RECEIVED
MAR 1 1965
U.S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO