

NM OIL CONSERVATION COMMISSION  
Drawer BD  
Artesia, NM 88210

Form 9-331  
Dec. 1973

Form Approved.  
Budget Bureau No. 42-R1424

C/SF

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well ☐ gas ☐ well ☐ other ☐ SWD  
2. NAME OF OPERATOR ☒ Ray Westall  
3. ADDRESS OF OPERATOR Box 4 Loco Hills NM 88255 D.  
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 1980 FSL & 660 FEL  
AT TOP PROD. INTERVAL:  
AT TOTAL DEPTH: Same

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☐  
REPAIR WELL ☐  
PULL OR ALTER CASING ☐  
MULTIPLE COMPLETE ☐  
CHANGE ZONES ☐  
ABANDON\* Re entry ☒  
(other) \_\_\_\_\_

SUBSEQUENT REPORT OF:

☐  
☐  
☐  
☐  
☐  
☐  
☐  
☐  
☐  
☐

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

We propose to re enter this well for water disposal to a depth of 2500 feet

Procedure will be by the enclosed plan of the New Mexico Oil Conservation Division Order No. R-8173

Subject to  
Like Approval  
by State

Posted ID-1  
11-21-86

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Ray Westall Owner TITLE \_\_\_\_\_ DATE 4/13/85

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE 11-12-86  
CONDITIONS OF APPROVAL, IF ANY:

STATE OF NEW MEXICO  
ENERGY AND MINERALS DEPARTMENT  
OIL CONSERVATION DIVISION

IN THE MATTER OF THE HEARING  
CALLED BY THE OIL CONSERVATION

DIVISION FOR THE PURPOSE OF  
CONSIDERING:

CASE NO. 8730

Order No. R-8173

APPLICATION OF RAY WESTALL FOR  
SALT WATER DISPOSAL, EDDY COUNTY,

NEW MEXICO

ORDER OF THE DIVISION

BY THE DIVISION:

This cause came on for hearing at 8:15 a.m. on November 21, 1985, at Santa Fe, New Mexico, before Examiner Michael E. Stogner.

NOW, on this 14th day of March, 1986, the Division Director, having considered the testimony, the record, and the recommendations of the Examiner, and being fully advised in the premises,

FINDS THAT:

(1) Due public notice having been given as required by law, the Division has jurisdiction of this cause and the subject matter thereof.

(2) The applicant, Ray Westall, seeks the authority to utilize the Texas Crude Oil Company Tennessee Federal Well No. 1 located 1980 feet from the South line and 660 feet from the East line (Unit I) of Section 21, Township 19 South, Range 31 East, NMPM, North Hackberry Yates-Seven Rivers Pool, Eddy County, New Mexico, for salt water disposal.

(3) The applicant proposes to utilize said well to dispose of produced salt water into the Seven Rivers formation, with injection into the perforated interval from approximately 2420 feet to 2491 feet and into the open-hole interval from approximately 2491 feet to 2581 feet.

(4) Injection should be accomplished through 2 3/8-inch plastic lined tubing installed in a packer set at approximately 2400 feet; the casing-tubing annulus should be filled with an inert fluid; and a pressure gauge or approved leak detection device should be attached to the annulus in order to determine leakage in the casing, tubing, or packer.

(5) Prior to commencing injection operations, the casing in the subject well should be pressure-tested throughout the interval from the surface down to the proposed packer setting depth, to assure the integrity of such casing.

(6) The injection well or system should be equipped with a pressure limiting switch or other acceptable device which will limit the wellhead pressure on the injection well to no more than 485 psi.

(7) The Director of the Division should be authorized to administratively approve an increase in the injection pressure upon a proper showing by the operator that such higher pressure will not result in migration of the injected waters from the Seven Rivers formation.

(8) The operator should give advance notification to the supervisor of the Artesia district office of the Division of the date and time of the installation of disposal equipment and of the mechanical integrity pressure test in order that the same may be witnessed.

(9) The operator should take all steps necessary to ensure that the injected water enters only the proposed injection interval and is not permitted to escape to other formations or onto the surface.

(10) Approval of the subject application will prevent the drilling of unnecessary wells and otherwise prevent waste, protect correlative rights, and protect fresh water resources.

IT IS THEREFORE ORDERED THAT:

(1) The applicant, Ray Westall, is hereby authorized to utilize Texas Crude Oil Company Tennessee Federal Well No. 1, located 1980 feet from the South line and 660 feet from the East line (Unit I) of Section 21, Township 19 South, Range 31 East, NMPM, North Hackberry Yates-Seven Rivers Pool, Eddy County, New Mexico, to dispose of produced salt water into the Seven Rivers formation, injection to be accomplished through 2 3/8-inch tubing installed in a packer set at approximately 2400 feet, with injection into the perforated interval from approximately 2420 feet to 2491 feet and into the open-hole interval from approximately 2491 feet to 2581 feet;

PROVIDED HOWEVER THAT, said tubing shall be internally plastic-lined; the casing-tubing annulus shall be filled with an inert fluid; and a pressure gauge shall be attached to the annulus or the annulus shall be equipped with an approved leak

detection device in order to determine leakage in the casing, tubing, or packer.

PROVIDED FURTHER THAT, prior to commencing injection operations, the casing in the subject well shall be pressure-tested to assure the integrity of such casing in a manner that is satisfactory to the supervisor of the Division's district office at Artesia.

(2) The injection well or system shall be equipped with a pressure limiting switch or other acceptable device which will limit the wellhead pressure on the injection well to no more than 485 psi.

(3) The Director of the Division may authorize an increase in injection pressure upon a proper showing by the operator of said well that such higher pressure will not result in migration of the injected fluid from the Seven Rivers formation.

(4) The operator shall notify the supervisor of the Artesia district office of the Division in advance of the date and time of the installation of disposal equipment and of the mechanical integrity pressure test in order that the same may be witnessed.

(5) The operator shall immediately notify the supervisor of the Division's Artesia district office of the failure of the tubing, casing, or packer, in said well or the leakage of water from or around said well and shall take such steps as may be timely and necessary to correct such failure or leakage.

(6) The applicant shall conduct disposal operations and submit monthly reports in accordance with Rules 702, 703, 704, 705, 706, 708, and 1120 of the Division Rules and Regulations.

(7) Jurisdiction of this cause is retained for the entry of such further orders as the Division may deem necessary.

DONE at Santa Fe, New Mexico, on the day and year hereinabove designated.

STATE OF NEW MEXICO  
OIL CONSERVATION DIVISION



R. L. STAMETS,  
Director

S E A L