Form 3160-5 (July 1989)		STATES	OFFICE FO. (BER OF COPLES REQUIRED (Other Instructions on re	BLM Roswell District Hodified Form No. <u>N1060-3160-4</u> 5. LEARE DESIGNATION AND SER	
(Formerly 9-331)	DEPARTMENT OF		V verse mue)	NM0107697	
	BUREAU OF LAND			6. IF INDIAN, ALLOTTEE OR TRIB	B N
SUNI (Do not use this i	DRY NOTICES AND form for proposals to drill or Use "APPLICATION FOR PE	D REPORIS ON to deepen or plug back RMIREC or such propos	WELLS to a different reservoir. sals.)		
I. OIL X GAR WELL X WELL [ОТНЕВ	MAY - 8 1991		7. UNIT AGREEMENT NAME 8. FARM OR LEASE NAME	
2. NAME OF OPERATOR	/		3a. Area Code & Phone No		
Mack Energy C	orporation \checkmark	O. C. D. ARTESIA, OFFICE	(505) 748-3436	Ohio Jones 9. WHLL NO.	
Beet Office B	ox 276, Artesia, N	Jew Mexico 88	210	#6	
LOCATION OF WELL (Re See also space 17 below	eport location clearly and in a	cordance with any Stat	e requirements.*	10. FIELD AND POOL, OR WILDCA	T
At surface				Lusk Yates 11. SBC., T., B., M., OB BLE. AND	. <u> </u>
Unit B, 660 f East line.	eet from the North	n line and 1980) feet from the	Sec 24-T19S-R31E	
14. PERMIT NO.	15. ELEVATIO	NS (Show whether DF, RT,	OR, etc.)	12. COUNTY OR PARISE 18. STA	ATE
				Eddy NM	
	Check Appropriate Br	ox To Indicate Natu	re of Notice, Report, or (Other Data	
	OTICE OF INTENTION TO :			UENT REPORT OF :	
			WATER SHUT-OFF	BEPAIRING WELL	
TEST WATER SHUT-OF Fracture treat	PULL OR ALTER	1	FRACTURE TREATMENT	ALTERING CABING	
RHOUT OR ACIDIZE	ABANDON*		SHOOTING OR ACIDIZING	ABANDON MENT [®]	X
REPAIR WELL	CHANGE PLANS		(Other)	s of multiple completion on Well	
(Other)			Completion or Recourt	pletion Report and Log form.) 1. Including estimated date of star 2. depths for all markers and sou	ting
I Lug and abane	loned as follows:				
Ran in ho of Class 1000'. I 25 sacks	ole with 7" sv ret C cement. Mix mu Perforate casing a cement out braden	d laden fluid a t 1050'. Pump head and left	tainer at 1150'. S and spot 150' plug 275 sacks Class C 7" casing full of c	Squeeze with 125 sack on bottom from 1150- Neat. Circulate cement. Installed	S
Ran in ho of Class 1000'. I 25 sacks	ole with 7" sv ret C cement. Mix mu Perforate casing a	d laden fluid a t 1050'. Pump head and left	and spot 150' plug 275 sacks Class C	Neat. Circulate	S
Ran in ho of Class 1000'. I 25 sacks	ole with 7" sv ret C cement. Mix mu Perforate casing a cement out braden	d laden fluid a t 1050'. Pump head and left	and spot 150' plug 275 sacks Class C	Neat. Circulate	S
Ran in ho of Class 1000'. I 25 sacks	ole with 7" sv ret C cement. Mix mu Perforate casing a cement out braden	d laden fluid a t 1050'. Pump head and left	and spot 150' plug 275 sacks Class C	Neat. Circulate	S
Ran in ho of Class 1000'. I 25 sacks	ole with 7" sv ret C cement. Mix mu Perforate casing a cement out braden	d laden fluid a t 1050'. Pump head and left	and spot 150' plug 275 sacks Class C	Neat. Circulate	S
Ran in ho of Class 1000'. I 25 sacks	ole with 7" sv ret C cement. Mix mu Perforate casing a cement out braden	d laden fluid a t 1050'. Pump head and left	and spot 150' plug 275 sacks Class C	Neat. Circulate	S
Ran in ho of Class 1000'. I 25 sacks	ole with 7" sv ret C cement. Mix mu Perforate casing a cement out braden	d laden fluid a t 1050'. Pump head and left	and spot 150' plug 275 sacks Class C	Neat. Circulate	S
Ran in ho of Class 1000'. I 25 sacks	ole with 7" sv ret C cement. Mix mu Perforate casing a cement out braden	d laden fluid a t 1050'. Pump head and left	and spot 150' plug 275 sacks Class C	Neat. Circulate	S
Ran in ho of Class 1000'. I 25 sacks	ole with 7" sv ret C cement. Mix mu Perforate casing a cement out braden	d laden fluid a t 1050'. Pump head and left	and spot 150' plug 275 sacks Class C	Neat. Circulate	S
Ran in ho of Class 1000'. I 25 sacks	ole with 7" sv ret C cement. Mix mu Perforate casing a cement out braden	d laden fluid a t 1050'. Pump head and left	and spot 150' plug 275 sacks Class C	Neat. Circulate	S
Ran in ho of Class 1000'. I 25 sacks	ole with 7" sv ret C cement. Mix mu Perforate casing a cement out braden	d laden fluid a t 1050'. Pump head and left	and spot 150' plug 275 sacks Class C	Neat. Circulate	S
Ran in ho of Class 1000'. H 25 sacks dry hole	ole with 7" sv ret C cement. Mix mu Perforate casing a cement out braden	d laden fluid a t 1050'. Pump head and left d location.	and spot 150' plug 275 sacks Class C 7" casing full of (on bottom from fibu- Neat. Circulate cement. Installed Port ID-2 5-(2-9) $\varphi \neq H$	-
Ran in ho of Class 1000'. H 25 sacks dry hole	ole with 7" sv reta C cement. Mix mu Perforate casing a cement out braden marker and cleane	d laden fluid a t 1050'. Pump head and left d location.	and spot 150' plug 275 sacks Class C	Neat. Circulate	-
Ran in ho of Class 1000'. H 25 sacks dry hole	the foregoing in true and corr	d laden fluid a t 1050'. Pump head and left d location.	and spot 150' plug 275 sacks Class C 7" casing full of (on bottom from 1150- Neat. Circulate cement. Installed $p_{of} ID-2$ 5-(2-9) $p \neq H$ DATE March 26, 1	-
Ran in ho of Class 1000'. H 25 sacks dry hole IR. I hereby certile that SIGNED (This space for Feder APPROVED BY	the foregoing is true and corr al or State office use)	d laden fluid a t 1050'. Pump head and left d location.	and spot 150' plug 275 sacks Class C 7" casing full of (on bottom from fibu- Neat. Circulate cement. Installed Port ID-2 5-(2-9) $\varphi \neq H$	-
Ran in ho of Class 1000'. H 25 sacks dry hole IR. I hereby certile that SIGNED (This space for Feder	the foregoing is true and corr al or State office use)	d laden fluid a t 1050'. Pump head and left d location.	and spot 150' plug 275 sacks Class C 7" casing full of (on bottom from 1150- Neat. Circulate cement. Installed $p_{of} ID-2$ 5-(2-9) $p \neq H$ DATE March 26, 1	-

must 19 IIS C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the