

(SUBMIT IN TRIPLICATE)

Las Cruces

Land Office 029358

Lease No. \_\_\_\_\_

Unit \_\_\_\_\_

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

RECEIVED

SEP 2 1967

SUNDRY NOTICES AND REPORTS ON WELLS

G. E. C.  
ARTESIA, OFFICE

NOTICE OF INTENTION TO DRILL.....		SUBSEQUENT REPORT OF WATER SHUT-OFF.....	
NOTICE OF INTENTION TO CHANGE PLANS.....		SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.....	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....		SUBSEQUENT REPORT OF ALTERING CASING.....	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.....		SUBSEQUENT REPORT OF REDRILLING OR REPAIR.....	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....		SUBSEQUENT REPORT OF ABANDONMENT.....	
NOTICE OF INTENTION TO PULL OR ALTER CASING.....	X	SUPPLEMENTARY WELL HISTORY.....	
NOTICE OF INTENTION TO ABANDON WELL.....			

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

Jones ..... July 15, 1947

Well No. 7 is located 2310 ft. from  $\begin{matrix} X \\ S \end{matrix}$  line and 330 ft. from  $\begin{matrix} E \\ W \end{matrix}$  line of sec. 24

NE $\frac{1}{4}$ , SE $\frac{1}{4}$  of 24 ..... 19S ..... 31E ..... N19M

( $\frac{1}{4}$  Sec. and Sec. No.) (Twp.) (Range) (Meridian)

Lusk ..... Eddy ..... New Mexico

(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is 3547 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Will fill hole to bottom of casing and set a cement plug in the bottom of the casing, then will cut the casing and recover all possible. Will then set a cement plug where the casing is cut. When casing is recovered, will set another cement plug approximately 15' below the base of the salt then will fill the hole to the top of the salt and on up into the 8" casing where we will set another cement plug. Will then recover as much of the 8" as possible and at the top of the hole will set the usual cement plug and marker.

T.D. 2876. Plugged back to 2650. 7" casing cemented at 2523'. Plug at top of salt will consist of 15 sax of cement & 10 sax will be used for each of the other plugs. Intervals between plugs will be filled with heavy mud.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Plains Production Company

Address 1110 Tower Petroleum Building  
Dallas 1, Texas

RECEIVED  
GEOLOGICAL SURVEY  
By *W. L. Cooper*  
W. L. Cooper

Title Agent