

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT
Artesia, NM 88210

NM OFFICE IN TRIPLI
(Other Instructions)
FOLLOW THESE

FE-
STON

Form approved
Budget Bureau No. 1004-0135
Expires August 31, 1985
LEASE DESIGNATION AND SERIAL NO

ckf

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT--" for such proposals.)

1. OIL WELL ☐ GAS WELL ☐ OTHER RE-ENTRY: DEEPEN, CONVERT TO SWD ☒

2. NAME OF OPERATOR
YATES PETROLEUM CORPORATION

3. ADDRESS OF OPERATOR
105 South 4th St., Artesia, NM 88210

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below.)
At surface
1980' FSL & 660' FEL, NE/SE, Sec. 3-20S-24E

SEP 13 '89

O.C.D.
ARTESIA, OFFICE

NM-58143
6. IF INDIAN, ALLOTTEE OR TRIBE NAME

N/A
7. UNIT AGREEMENT NAME

N/A
8. FARM OR LEASE NAME

Bate Federal
9. WELL NO.

1
10. FIELD AND POOL, OR WILDCAT

Wildcat
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Unit I, Sec. 3-T20S-R24E

14. PERMIT NO.
API #30-015-05912

15. ELEVATIONS (Show whether DF, RT, GR, etc.)
3691' GR

12. COUNTY OR PARISH
Eddy

13. STATE
NM

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
(Other) ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
ABANDON* ☐
CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐
FRACTURE TREATMENT ☐
SHOOTING OR ACIDIZING ☐
(Other) Deepen well, perforate, treat ☒
(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) *

8-1-89. Dug out wellhead. RUPU and reverse unit. Ray Stall, YPC, notified Shannon Shaw, BLM, Carlsbad, NM, of spud. Drilled, washed and cleaned out to old TD 4220'. Drilled new hole from 4220-4500' (280'). Ran float shoe, 31 jts 5 1/2" casing, DV tool and additional 18 jts 5 1/2" casing. Shoe set 4524', DV tool set 3219'. Cmt'd 1st stage w/300 sx Class C w/.5% CF-14, 5#/sx Salt, 1/2#/sx Celloseal. PD 4:00 AM 8-8-89. Open DV tool. Circulated out 30 sx cement. Cmt'd 2nd stage w/475 sx Pacesetter Lite + 150 sx Class C + 2% CaCl2. PD 9:00 AM. Circulated 75 sx to surface.

8-8-89. Permission obtained by Ray Stall, YPC, from Shannon Shaw, BLM, Carlsbad, NM and Johnny Robinson, NMOC, Artesia, NM, to drill DV tool and shoe to 4550' and complete with 26' of open hole (4524-4550'). Approved under existing SWD Order #371.

8-10-89. TIH and drilled cement and DV tool. Cleaned out to TD 4550'. Perforated 1st stage w/54 holes as follows: 4469-72' (2 SPF); 4480-82' (2 SPF); 4489-91' (2 SPF); 4500-03' (2 SPF); 4510-12' (2 SPF); 4516-22' (4 SPF). (Hole size-.42")

8-11-89. Perforated 2nd stage 4238-4298' w/19 - .42" holes as follows: 4238, 39, 40, 49, 50, 51, 55, 57, 58, 59, 61, 69, 70, 72, 73, 74, 96, 97, and 4298'. Perforated 3rd stage 4338-4426' w/23 - .42" holes as follows: 4338, 39, 44, 45, 48, 57, 58, 59, 60, 61, 62, 91, 92, 93, 94, 95, 4411, 12, 13, 19, 20, 25 and 4426'. Acidized perforations 4469-4522'; 4238-4298'; and 4338-4426' in three separate stages with 25000 gals 20% NEFE acid. Waiting on permanent SWD equipment. Testing well.

18. I hereby certify that the foregoing is true and correct

SIGNATURE *John Antonio Goodlett*

TITLE Production Supervisor

DATE 8-15-89

(This space for Federal or State office use)

APPROVED BY
CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

*See Instructions on Reverse Side

SJS