

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO. 30-015-05917
5. Indicate Type of Lease STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>
6. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER	7. Lease Name or Unit Agreement Name Thomas
2. Name of Operator YATES PETROLEUM CORPORATION	8. Well No. 1
3. Address of Operator 105 South Fourth Street - Artesia, NM 88210	9. Pool name or Wildcat Penasco Draw San Andres Yeso

4. Well Location Unit Letter <u>H</u> : <u>1980</u> Feet From The <u>North</u> Line and <u>660</u> Feet From The <u>East</u> Line
Section <u>8</u> Township <u>19S</u> Range <u>25E</u> NMPM <u>Eddy</u> County
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 3451' GR

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>
OTHER: <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
	CASING TEST AND CEMENT JOB <input type="checkbox"/>
	OTHER: <input type="checkbox"/>

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Proposed to plug and abandon as follows: (Approved by OCD November 22, 1993-- Ray Smith)

1. Pull tubing.
2. Run tubing to 2954' (PBTD).
3. Load hole with 10#/gallon brine containing 25#/bbl salt gel.
4. Set 206 sacks Class "C" 2% CaCl2 plug from 2575-535'.
5. Set 10 sack surface plug and install regulation abandonment marker.

NOTE: After reviewing well file, it was found that in September, 1990, well was rigged up on for a pump change. The rods and pump were pulled from the well. The tubing was then pulled and found to be parted. WIH w/overshot and could not get past 1200'. Pulled over-shot and run 3-1/4" OD swedge w/6 3-1/8" drill collars and swedged out to 1225'. Run 3-1/2" swedge to 1230'. Ran 3-7/8" swedge to 1320'. Ran 3-7/8" OD overshot to 1235'. Did not catch fish. Ran 3-1/2" impression block. Ran 2" spear. Did not catch fish. Ran 3-5/8"

CONTINUED:

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE <u>Rusty Klein</u>	TITLE <u>Production Clerk</u>	DATE <u>Feb. 24, 1994</u>
TYPE OR PRINT NAME <u>Rusty Klein</u>		TELEPHONE NO. <u>505-748-1471</u>

(This space for State Use)

APPROVED BY <u>[Signature]</u>	TITLE <u>OIL AND GAS INSPECTOR</u>	DATE <u>2-24-94</u>
--------------------------------	------------------------------------	---------------------