

APPROVED
(Feb. 1961)JAN 30 1963
RONNIE E. SHOOK
ACTING DISTRICT ENGINEER

(SUBMIT IN TRIPPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office

Lease No.

Unit

NM 04560

RECEIVED

FEB 1 1963

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT OFF
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR
NOTICE OF INTENTION TO SHUT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT
NOTICE OF INTENTION TO PILL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY
NOTICE OF INTENTION TO ABANDON WELL	

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

January 21, 1963

Pecos River Deep Unit

Well No. 1 is located 1980 ft. from ~~(N)~~ line and 1980 ft. from ~~(E)~~ line of sec. 28S44 NW4 28
(Sec and Sec. No.)198 27E
(Twp.) (Range)N.M.P.M.
(Meridian)Wildcat
(Field)Bddy
(County or Subdivision)New Mexico
(State or Territory)

The elevation of the derrick floor above sea level is ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

1/17/63

1. Run 90 jts 9 5/8" casing as follows:

2 jts 9 5/8" 36# N-40 8 RD THD	60.65
70 jts 9 5/8" 32.30# N-40 8 RD THD	2196.41
18 jts 9 5/8" 36.00# N-40 8 RD THD	<u>543.97</u>
	2801.03

Set @ 2783' T.D.

2. Cemented 1st stage w/350 sac incoor regular 2% calcium chloride and 150 units NYS-400 (1,155 ft
- ³
-).

3. Set DV packer collar @ 799'. Fluid circulated immediately, cemented w/100 units NYS-400 (770 ft
- ³
-) and 100 sac incoor

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company

Address

By

Title