	(SUBMIT IN TRIPLICATE)
6 1964	UNITED STATES
JAN VE	DEPARTMENT OF THE INTERIOR
	GEOLOGICAL SURVEY
D. S.	
SUNDRY NO	OTICES AND REPORTS ON WELLS
NOTICE OF INTENTION TO DRILL	
NOTICE OF INTENTION TO CHANGE PLANS.	WATER SHUT-OFF
NOTICE OF INTENTION TO TEST WATER SH	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING
NOTICE OF INTENTION TO RE-DRILL OR RE	
NOTICE OF INTENTION TO SHOOT OR ACID	ON IL-DRILLING OR REPAIR.
NOTICE OF INTENTION TO PULL OR ALTER	CONSCIONT REPORT OF ABANDONMENT
NOTICE OF INTENTION TO ABANDON WELL	CASING SUPPLEMENTARY WELL HISTORY
WELL	
(INDICATE ABO	DVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)
:(a ¹)	
A Some Patron	January 10, 1
Jones-Federal	
Well No. 2 is located	1980 4 from (K) 1 1 660 c c (E)
is invator	1980 ft. from $\begin{cases} E \\ S \end{cases}$ line and 660 ft. from $\begin{cases} E \\ S \end{cases}$ line of sec
(14 Bec. and Sec. No.)	(Twp.) (Range) (Meridian)
Lunk (Stramm)	(Iwp.) (Range) (Meridian)
(Field)	(County of Subdivision)
(=2)	(State or Territory)
(=2)	above sea level is
The elevation of the derrick floor (State names of and expected depths to objection Drill with Rotary tools as 17 ¹ hole to 500'. Set 13 11" hole to 500'. Set 3- 11" hole to 500'. Set 3- 7-7/8" hole to 11,600'. Set Perforate with 2 holes per Run 2" SUE tubing. Acidim	above sea level is
The elevation of the derrick floor (State names of and expected depths to objection Drill with Rotary tools as 17 ¹ hole to 500'. Set 13 11" hole to 500'. Set 3- 11" hole to 500'. Set 3- 7-7/8" hole to 11,600'. Set Perforate with 2 holes per Run 2" SUE tubing. Acidim	above sea level is
The elevation of the derrick floor (State names of and expected depths to objection Drill with Rotary tools as 17 ¹ hole to 500'. Set 13 11 ⁿ hole to 4200'. Set 8- 7-7/8" hole to 11,600'. Set Perforate with 2 holes per Run 2" EUE tubing. Aridian	above sea level isft. DETAILS OF WORK ive sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, co se points, and all other important proposed work follows: -3/8" new casing & cement to surface. 5/8" new casing & cement to surface. 5/8" new casing & cement to surface. * of the foot in Stream pay. * with 500 gallons MCA for completion of the full with the full of th
The elevation of the derrick floor (State names of and expected depths to objection Drill with Rotary tools as 17 ¹ hole to 500'. Set 13 11" hole to 500'. Set 3- 11" hole to 500'. Set 3- 7-7/8" hole to 11,600'. Set Perforate with 2 holes per Run 2" SUE tubing. Acidim	above sea level isft. DETAILS OF WORK ive sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, co se points, and all other important proposed work follows: -3/8" new casing & cement to surface. 5/8" new casing & cement to surface. 5/8" new casing & cement to surface. * of the foot in Stream pay. * with 500 gallons MCA for completion of the full with the full of th
The elevation of the derrick floor (State names of and expected depths to objection Drill with Rotary tools as 17 ¹ hole to 500'. Set 13 11 ⁿ hole to 4200'. Set 8- 7-7/8" hole to 11,600'. Set Perforate with 2 holes per Run 2" EUE tubing. Aridian	above sea level isft. DETAILS OF WORK ive sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, co se points, and all other important proposed work follows: -3/8" new casing & cement to surface. 5/8" new casing & cement to surface. 5/8" new casing & cement to surface. * of the foot in Stream pay. * with 500 gallons MCA for completion of the full with the full of th
The elevation of the derrick floor (State names of and expected depths to objection Drill with Rotary tools as 17 ¹ hole to 500'. Set 13 11 hole to 500'. Set 3- 17 ¹ hole to 4200'. Set 3- 7-7/8" hole to 11,600'. Set Perforate with 2 holes per Run 2" EUE tubing. Acidim I understand that this plan of work must rec Company	above sea level isft. DETAILS OF WORK ive sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, co se points, and all other important proposed work follows: -3/8" new casing & cement to surface. 5/8" new casing & cement to surface. 5/8" new casing & cement to surface. * of the foot in Stream pay. * with 500 gallons MCA for completion of the full with the full of th
The elevation of the derrick floor (State names of and expected depths to objection Drill with Rotary tools as 17 ¹ hole to 500'. Set 13 11 ² hole to 500'. Set 3- 11 ³ hole to 4200'. Set 3- 7-7/8" hole to 11,600'. Set Perforate with 2 holes per Run 2" EUE tubing. Azidisc I understand that this plan of work must recompany DELHI-TAYLOR OIL	above sea level is _3542_ft. DETAILS OF WORK ive sands; show sizes, weights, and lengths of proposed casings; indicate muddle jobs, co points, and all other important proposed work? follows: -3/8" new casing & cement to surface. 5/8" new casing & cement
The elevation of the derrick floor (State names of and expected depths to objection (State names of and expected depths to objection Drill with Rotary tools as 17 ¹ hole to 500'. Set 13 11 ² hole to 500'. Set 3- 7-7/8" hole to 11,600'. Set 3- 7-7/8" hole to 11,600'. Set 3- 7-7/8" hole to 11,600'. Set 3- Perforate with 2 holes per Run 2" EUE tubing. Acidim I understand that this plan of work must rec Company	above sea level isft. DETAILS OF WORK ive sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, co se points, and all other important proposed work follows: -3/8" new casing & cement to surface. 5/8" new casing & cement to surface. 5/8" new casing & cement to surface. * of the foot in Stream pay. * with 500 gallons MCA for completion of the full with the full of th