

c/5F

Form 3160-5
(June 1990)

RECEIVED
JUN 7 10 49 AM '95

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

5. Lease Designation and Serial No.

NMNM-0107697

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Jones "B" Fed. No. 1

9. API Well No.

30-015-10056

10. Field and Pool, or Exploratory Area

Lusk Strawn

11. County or Parish, State

Eddy, New Mexico

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

Lynx Petroleum Consultants, Inc.

3. Address and Telephone No.

P.O. Box 1979, Hobbs, NM 88241 (505) 392-6950

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

1980' FSL & 660' FEL
Section 25, T-19S, R-31E

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent
☒ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment
☒ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☐ Other
- ☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

1. Located 5½" casing stub at 3960'. Tested liner lap to 700 psi. O.K.

2. Set a CIBP @ 6100' with 35' of cement. (Verbal Approval from Mr. Adam Salameh)

3. Perforated 5½" @ 4728' and set a cement retainer 12'. Could not squeeze.

4. Perforated Delaware 4686-4700'. Acidized with 1500 gals 7½% HCl. Swabbed water.

5. Perforated Delaware 4416-30' and 4448'. Acidized with 1500 gals. 7½% HCl. Swabbed water.

6. Review for P&A.

14. I hereby certify that the foregoing is true and correct

Signed

Mac

Title

President

Date

6/5/95

(This space for Federal or State office use)

Approved by

Title

3 1995 Date
SJS

Conditions of approval, if any: