

RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto

TOOLS USED

Rotary tools were used from 0 feet to 1951 KB feet, and from feet to feet.
Cable tools were used from feet to feet, and from feet to feet.

PRODUCTION

Put to Producing June 28, 1963

OIL WELL: The production during the first 24 hours was 40 barrels of liquid of which 100% was oil. 0% was emulsion; 0% water; and 0% was sediment. A.P.I. Gravity 37°

GAS WELL: The production during the first 24 hours was M.C.F. plus barrels of Liquid Hydrocarbon. Shut-in pressure lbs.

Length of Time Shut in

PLEASE INDICATE BELOW FORMATION TOPS (IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE):

Southern New Mexico			Northwestern New Mexico		
T. Anhydrite			T. Devonian		T. Ojo Alamo
T. Salt			T. Silurian		T. Kirtland-Fruitland
T. Salt			T. Montoya		T. Farmington
T. Yates	377'		T. Simpson		T. Pictured Cliffs
T. Red sand	632'		T. McKee		T. Menefee
T. Queen	1200'		T. Ellenburger		T. Point Lookout
T. Dolomite	1617'		T. San Wash		T. Mancos
T. Sandstones	1924'		T. Granite		T. Dakota
T. Glomero			T. Premier	1890'	T. Morrison
T. Dolomite					T. Penn.
T. Red sand					
T. Anhydrite					
T. Dolomite					
T. Sandstones					
T. Miss.					

FORMATION RECORD

From	To	Formation	From	To	Thickness in Feet	Formation
0	110	110				
110	377	267				
377	450	73				
450	632	182				
632	1200	568				
1200	1245	45				
1245	1617	372				
1617	1890	273				
1890	1924	34				
1924	1951	27				

ATTACH SEPARATE SHEET IF ADDITIONAL SPACE IS NEEDED

I hereby swear or affirm that the information furnished herein is a complete and correct record of the well and all work done on it so far as can be determined from available records.

June 28, 1963

(Date)

Company or Operator International-Yates Address P.O. Box 427, Artesia, New Mexico
Name [Signature] Position Title District Engineer