

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRI-STATE
(Other instructions on re-
ference 100)

Form approved.
Budget Bureau No. 1004-0135
Expires August 31, 1985

458

5. LEASE DESIGNATION AND SERIAL NO.

NM-067896

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Keohane et al "D" Federal

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Shugart (Y, SR, Q, G)

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 19, T18S, R31E

12. COUNTY OR PARISH

Eddy

13. STATE

NM

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

Southland Royalty Company ✓

AUG 16 '89

3. ADDRESS OF OPERATOR

21 Desta Drive, Midland, Texas 79705

O. C. D.

ARTESIA, OFFICE

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

660' FSL & 1980' FEL, Sec. 19, T18S, R31E

W. D.

14. PERMIT NO.

Approved 6/13/88

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3633 DF

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETION

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) *

6/20/89

MIRU Plugging Unit. NUBOP. Set CIBP @ 3350'. Cap w/ 35' Cmt. RIH w/ Tbg. Open ended to 3000'. Disp. hole w/ 9 lb. mud-laden brine. POH to 2000'. Test 4½" Csg. to 500 psi. Spot 20 sx Cl. "C" w/ 2% CaCl₂. Cmt. plug from 2000'-1281'. TOH. SDFN. WOC.

6/21/89

RIH w/ Tbg. Tag cmt. plug @ 1678'. POH to 741'. Spot 10 sx cmt. plug 741' - 597'. POH to 270'. Spot 25 sx Cmt. plug from 270' - Surface. ND BOP. Cut off well head. Install dry hole marker. RD PU

Dale Carpenter, BLM, was on-site during this work.

Post ID-2
8-18-89
P & A

RECEIVED

18. I hereby certify that the foregoing is true and correct

SIGNED

Robert L. Bradshaw

TITLE

Sr. Staff Env./Reg. Spec.

DATE

7/27/89

(This space for Federal or State office use)

APPROVED BY

Shannon J. Shaw

FOR:

TITLE

OWNER, MINERAL RESOURCES

DATE

8-15-89

CONDITIONS OF APPROVAL, IF ANY:

Applied as to plugging of the well bore.
Liability under bond is retained until
surface restoration is completed.

*See Instructions on Reverse Side